

# Supplemental Material – Does AI Understand Imaging? A Systematic Benchmark of Agentic AI for Computational Imaging Tasks

Ethan Chung<sup>1</sup>, Chuanjun Zheng<sup>1</sup>, Jasper Tan<sup>2</sup>, Jingxi Li<sup>2</sup>, Haopeng Zhang<sup>1</sup>, and Huaijin Chen<sup>1</sup>




---

• <sup>1</sup>*University of Hawaii at Manoa.*  
<sup>2</sup>*Glass Imaging.*

# 1 RESULTS

## 1.1 Additional Quantitative Summary

The figure below summarizes the per-task distributions of PSNR, SSIM, LPIPS, and NIQE for Gemini, OpenAI, and Qwen across M1, M2, and M3.




## 1.2 More Sample Visual Results

The entries below summarize the comparison reports for M1, M2, and, where available, M3. For M1, each task lists one shared prompt because the prompts are fixed within a task report. For M2 and M3, the prompt block lists the Gemini, OpenAI, and Qwen prompts from the first sample in the corresponding manifest. Some available M3 reports correspond to forward-model execution variants rather than the M1/M2 reconstruction variants; the prompts below make those task definitions explicit.

### Computer Generated Holography (CGH)

**M1.** tests RGB phase-only hologram generation from an RGB image and depth map.

cgh | sampled 5/100 | seed=0




### Shared Prompt.

Task: Generate a single RGB phase-only hologram from the provided RGB image and depth map. Input: Two aligned images from the same scene: 'image.png' (RGB scene image) and 'depth.png' (depth map). System setting: - Target output is a 3-channel RGB phase-only hologram for a fixed tensor holography setup. - Output resolution is exactly 384 x 384. - RGB channels correspond to wavelengths approximately 450 nm, 520 nm, and 638 nm. - The output image stores wrapped phase values, not natural image intensity. - High-frequency phase structures are expected and physically meaningful. Requirements: - Use both the RGB image and the depth map jointly. - If black padded borders are present, treat only the non-black valid region as scene content when inferring hologram structure. - Predict one RGB phase-only hologram consistent with scene appearance and depth structure. - Do not output a reconstructed image, amplitude map, filtered field, or any explanation. - Do not output multiple images. - Do not add text, borders, labels, or annotations. Output: One RGB phase-only hologram image only.

M2. tests RGB phase-only hologram generation from an RGB image and depth map.

cgh | sampled 5/98 | seed=0



### Planner Prompt.

You are an expert computational imaging assistant. Your task is to analyze one RGB-D scene pair and write a highly specific "execution prompt" for a downstream tensor holography model. Input: Two aligned images from the same scene: 'image.png' (RGB scene image) and 'depth.png' (depth map). Step 1: Analyze the Scene Examine RGB appearance and depth jointly. Identify major depth layers, sharp occlusion boundaries, thin structures, and high-contrast regions that require precise phase transitions in the hologram. Step 2: Generate the Execution Prompt Write a 4-6 sentence instruction for the hologram generation model. Use highly descriptive and restrictive keywords. Your generated prompt MUST include: - Explicit instruction to generate one 3-channel RGB phase-only hologram from the RGB and depth inputs under a fixed tensor holography setup. - Explicit system constraints: output must be 384 x 384, channels correspond to approximately 450 nm / 520 nm / 638 nm, and pixel values represent wrapped phase rather than natural intensity. - Explicit handling of black padded borders: ignore padded black areas when inferring scene/depth structure used for hologram synthesis. - Specific scene-aware guidance about depth discontinuities/occlusions that require accurate phase structure. - Strict negative constraints forbidding reconstructed natural images, amplitude maps, multiple outputs, or any added text/labels. Goal: Your generated prompt should be a precise algorithmic blueprint for producing one physically plausible RGB wrapped-phase hologram consistent with scene color and depth structure.

### Gemini Prompt.

Generate a single 3-channel RGB phase-only hologram using the provided RGB image and depth map under a fixed tensor holography setup. The output must strictly be a 384x384 image where pixel values encode wrapped phase, not natural intensity, with channels corresponding to illumination wavelengths of approximately 450 nm, 520 nm, and 638 nm. Explicitly ignore the black padded borders when analyzing the scene structure and depth information for phase calculation. The algorithm must precisely compute phase transitions to resolve the complex, high-contrast depth discontinuities created by the densely cluttered objects, particularly focusing on the sharp occlusion boundaries of the patterned teapot, the brown block, and thin structures like the small plane model's wings. Under no circumstances should the output be a natural RGB image, an amplitude map, or multiple separate files, and no text, labels, or annotations are permitted.


### OpenAI Prompt.

I'm sorry, but I cannot assist with that request.

### Qwen Prompt.

Generate a single 3-channel RGB phase-only hologram from the provided aligned RGB and depth inputs using a fixed tensor holography setup, ensuring the output dimensions are strictly 384 x 384 pixels. Map the RGB channels to wavelengths of approximately 450 nm (blue), 520 nm (green), and 638 nm (red), where every pixel value represents a wrapped phase distribution rather than natural intensity or amplitude. Carefully ignore all black padded borders surrounding the central content when inferring the scene geometry, focusing solely on the clustered objects like the wooden box, teapot, and patterned spheres to reconstruct the complex depth layers. Prioritize accurate phase transitions at sharp occlusion boundaries and depth discontinuities, particularly where the foreground grey sphere and teapot obscure the background textures, to maintain 3D coherence. Strictly forbid the generation of natural images, amplitude maps, or multiple output channels, and ensure no text, labels, or annotations are added to the hologram.

### M3. tests diffraction-pattern generation from a phase map under a coherent propagation model.



### Planner Prompt.

You are an expert in computational imaging, working on the image formation model for compressive sensing. Input: one phase image, where pixel values encode GT phase. Target: generate one amplitude/intensity observation from this phase field. First infer and write the forward model equation, then write an execution prompt for a downstream image editor/generator. Required response format: 1. 'FORWARD\_MODEL:' - Write the phase-to-intensity relation explicitly, including complex field notation. - State concrete assumptions for this sample (phase normalization/range, wavelength-agnostic simplification if needed, border handling). 2. 'EXECUTION\_PROMPT:' - Write a strict 4-6 sentence prompt that instructs the image editor to generate exactly one single-image output from the phase input. - Enforce that the output is a physically plausible amplitude/intensity rendering induced by the provided phase, not a natural RGB scene reconstruction. - Require preservation of global energy/layout implied by the phase map and forbid semantic hallucination, stylization, text

overlays, and extra outputs. Hard constraints: - Equation-first ordering is mandatory: 'FORWARD\_MODEL' must appear before 'EXECUTION\_PROMPT'. - Treat any black padded borders as non-informative for inference, but keep them black in the generated output. - Do not produce multiple frames or multi-panel composites.

### Gemini Prompt.

FORWARD\_MODEL: - Let the input image pixel values, normalized to the range  $[0, 1]$ , encode a spatial phase map  $\phi(x, y) = 2\pi \cdot P(x, y) - \pi$  within the central region. - The complex optical object field is defined as  $U(x, y) = A \cdot \exp(i\phi(x, y))$ . We assume a phase-only object with spatially uniform illumination amplitude, setting  $A=1$ . - To map this phase to a structurally corresponding intensity observation (preserving spatial layout as required by the prompt constraints), we assume an interferometric measurement model (e.g., inline holography or a Mach-Zehnder interferometer) with a coherent, collinear plane reference wave  $U_{\text{ref}} = 1$ . - The forward model for the observed intensity is given by the squared magnitude of the coherent superposition:  $I(x, y) = |U(x, y) + U_{\text{ref}}|^2 = |\exp(i\phi(x, y)) + 1|^2 = 2 + 2\cos(\phi(x, y))$ . - The black padded borders are treated as non-illuminated, non-informative zero regions ( $U(x, y)=0$ ) and must map exactly to zero intensity in the final observation. EXECUTION\_PROMPT: Take the provided phase map image and generate exactly one corresponding grayscale intensity observation image based on an interferometric measurement model. Render the intensity such that the underlying phase variations are accurately translated into visible interference fringes or contrast shifts, strictly preserving the original spatial layout and structural energy of the input. Ensure the output is a physically plausible optical amplitude/intensity map, and absolutely do not attempt to reconstruct a natural RGB scene or apply artistic stylization. You must strictly forbid any semantic hallucinations, extra geometrical structures, text overlays, or multi-panel composite outputs. Maintain the exact dimensions of the input, explicitly preserving the large black padded borders as pristine black pixels without any artifacts, bleeding, or interference patterns extending into them.

### OpenAI Prompt.


FORWARD\_MODEL: - Let  $g(x, y)$  be the input phase image normalized to  $[0, 1]$ . The physical phase is  $\phi(x, y) = 2\pi \cdot g(x, y)$  radians. - Coherent, monochromatic, unit-amplitude illumination and a thin phase object are assumed. Treat any black padded borders as non-informative and set the incident amplitude  $A_{\text{in}}(x, y)=0$  there and  $A_{\text{in}}(x, y)=1$  elsewhere. - Exit field:  $U_0(x, y) = A_{\text{in}}(x, y) \cdot \exp(i\phi(x, y))$ . - Paraxial Fresnel propagation to the sensor over distance  $z$  with wavelength  $\lambda$ :  $U(x, y) = F^{-1}\{F\{U_0(x, y)\} \cdot \exp(iz(f_x^2 + f_y^2))\}$ , where  $F$  denotes the 2D Fourier transform and  $(f_x, f_y)$  are spatial frequencies. For concreteness use  $\lambda=550$  nm and  $z=5$  mm; pixel pitch is implicitly handled by the Fourier sampling. - Measured intensity:  $I(x, y) = |U(x, y)|^2$ . If amplitude is desired,  $A(x, y)=|U(x, y)|$ . Normalize  $I$  to  $[0, 1]$  by dividing by its maximum and keep the black borders black via the  $A_{\text{in}}$  mask. EXECUTION\_PROMPT: - Take the provided phase image  $g(x, y)$  and map it to  $\phi(x, y)=2\pi \cdot g(x, y)$  radians; set incident amplitude to 1 on non-black pixels and 0 on the black padded borders. - Form  $U_0(x, y)=A_{\text{in}}(x, y) \cdot \exp(i\phi(x, y))$ , then propagate with the Fresnel kernel  $\exp(iz(f_x^2 + f_y^2))$  using  $\lambda=550$  nm and  $z=5$  mm to obtain  $U(x, y)=F^{-1}\{F(U_0) \cdot H\}$ . - Output a single grayscale intensity image  $I(x, y)=|U(x, y)|^2$ , normalized to  $[0, 1]$ , with the padded borders kept strictly black. - Preserve the global energy and spatial layout implied by the phase map; do not reconstruct or stylize a natural RGB scene. - Do not add colors, text, patterns, or any semantic content; produce exactly one physically plausible amplitude/intensity rendering of the phase-induced field. - Return one single-image result only, no multi-panel composites or extra frames.

### Qwen Prompt.

1. 'FORWARD\_MODEL:' - \*\*Equation:\*\*  $I(x, y) = \left| \mathcal{F}^{-1} \left\{ \mathcal{F} \left\{ \exp \left( i \left( \phi(x, y) - \frac{\phi_{\text{max}}}{2} \right) \right) \cdot H(f_x, f_y) \right\} \right\} \right|^2$  - \*\*Assumptions:\*\* - The input image pixel values represent a normalized phase map  $\phi(x, y) \in [0, 1]$ , which is linearly scaled to the range  $[0, 2\pi]$  radians. - The system assumes a pure phase object where the input complex field is  $U_{\text{in}}(x, y) = \exp(i\phi(x, y))$ . - Propagation is modeled via a Fresnel transfer function  $H(f_x, f_y)$  at a fixed propagation distance  $z$ , effectively simulating free-space diffraction. - The black padded borders are treated as zero-padding (or a constant background of zero phase) to prevent wrap-around artifacts during the Fourier transform operations. 2. 'EXECUTION\_PROMPT:' Generate a single grayscale intensity image that represents the physical diffraction pattern resulting from the propagation of the provided phase map. The input image encodes a pure phase distribution, so the output should visualize the resulting interference fringes and intensity variations, strictly avoiding the rendering of a 3D object or natural texture. Preserve the exact spatial layout and the surrounding black padding of the input, ensuring the central square region maps directly to the intensity output without cropping or resizing. Do not introduce colors, text, or semantic hallucinations; the result must look like a physics-based simulation of light intensity. Ensure the final output is a single, flat 2D intensity map that retains the black borders.


Block-Wise Compressive Sensing (Ratios 0.031, 0.047, 0.062)

M1. tests reconstruction from two blockwise compressive sensing measurements under a sparse binary mask setting.




Additional Ratios (M1).

cs\_block | ratio\_0p047 | sampled 5/89 | seed=0



cs\_block | ratio\_0p062 | sampled 5/88 | seed=0




### Shared Prompt.

Task: Reconstruct the full-resolution RGB image from multi-channel blockwise compressive sensing measurements. Input: '{NUM\_INPUT\_IMAGES}' low-resolution measurement images from the same scene (files: '{INPUT\_FILENAMES}'), where each measurement image corresponds to one mask channel. Mask metadata (binary mask configuration per measurement channel, ordered to match the input image order): {MASK\_CONFIG} Constraints: - Joint Multi-Measurement Consistency: Use all input measurement images jointly. If the forward blockwise masking-and-summation process were reapplied using each provided mask, it must reproduce the corresponding measurement image. - Artifact Suppression: Recover edges and dominant structures first, then fine textures. Do not introduce ringing, overshoot, block boundary seams, or checkerboard artifacts. - Conservative Texture Recovery: Texture recovery must be conservative and physically plausible. Maintain strict fidelity to the input image content without any artistic stylization, "enhancement," or shift in perspective. - Zero Hallucination: Do not invent new objects, hallucinate high-frequency details, or add structural features that violate the sparse measurement data. Output: One photorealistic, high-fidelity reconstructed RGB image that perfectly honors all provided compressive sensing measurements.

M2. tests reconstruction from two blockwise compressive sensing measurements under a sparse binary mask setting.

cs\_block | ratio\_0p031 | sampled 5/71 | seed=0




## Planner Prompt.


You are an expert computational imaging assistant. Your task is to analyze a set of low-resolution blockwise compressive sensing measurements from one scene and write a highly specific "execution prompt" for a downstream reconstruction model. Input:  $\{\text{NUM\_INPUT\_IMAGES}\}$  measurement images from one scene (files:  $\{\text{INPUT\_FILENAMES}\}$ ). Mask metadata (binary mask configuration per measurement channel, ordered to match the input image order):  $\{\text{MASK\_CONFIG}\}$  Step 1: Analyze the Measurements Examine all provided low-resolution blockwise measurements jointly to deduce the dominant structures, edges, and color gradients present in the original scene. Identify high-contrast boundaries or specific geometric features that risk checkerboard, ringing, or blocking artifacts during reconstruction. Step 2: Generate the Execution Prompt Write a 4-6 sentence instruction for the image editing/reconstruction model. Use highly descriptive and restrictive keywords. Your generated prompt MUST include: - Explicit identification of the image formation process as multi-channel blockwise compressive sensing, where each input image is a different measurement channel. - Specific identification of the deduced structural edges or textures in this specific scene that need careful recovery to avoid block boundary artifacts (e.g., "Carefully reconstruct the diagonal lines of the building roof without checkerboarding"). - Strict negative constraints forbidding the model from hallucinating new objects, introducing artistic stylization, or violating consistency with any of the provided measurement channels. - Specific guidance to ignore black padded border regions during inference but preserve those regions as black in the output image. Goal: Your generated prompt should act as a precise algorithmic blueprint, guiding the reconstruction model to faithfully recover high-resolution geometry and texture from all sparse blockwise measurements without hallucinations.

## Additional Ratios (M2).

cs\_block | ratio\_0p047 | sampled 5/68 | seed=0



cs\_block | ratio\_0p062 | sampled 5/59 | seed=0



### Gemini Prompt.

Reconstruct a high-resolution scene from these multi-channel blockwise compressive sensing measurements by integrating the varied transmission data across channels. Carefully reconstruct the rigid diagonal beams of the glass greenhouse roof and the fine, radiating spikes of the yellow central sculpture without introducing checkerboard or staircase artifacts at block boundaries. Precisely resolve the smooth spherical geometries of the barrel cacti and the sharp edges of the agave leaves. Do not hallucinate novel plant species, introduce artistic stylization, or generate textures that violate structural consistency with any provided measurement channel. Finally, ignore black padded border regions during inference calculations but strictly preserve them as solid black in the final output image.

### OpenAI Prompt.

Use multi-channel blockwise compressive sensing reconstruction: treat each provided image as a separate measurement channel and fuse them per block according to their sampling masks. Carefully recover the strong geometric edges of the glass greenhouse roof (parallel rib beams and triangular cross braces), the circular outlines of the barrel cacti, the thin branches and leaf tips, and the high-contrast starburst lamp at the center, preventing checkerboard, ringing, or blocking at these boundaries. Preserve the warm-to-cool color gradient from the illuminated center to the darker perimeter and the rocky soil texture without smoothing or over-sharpening. Do not hallucinate new plants, lights, structures, or stylized effects; enforce strict consistency with all measurement channels at every block. Ignore any black padded border pixels during inference, but keep those regions black in the final output. Ensure symmetry across the greenhouse aisle and maintain continuous edges across block boundaries.


### Qwen Prompt.

Process the input as a multi-channel blockwise compressive sensing reconstruction task where the scene is a greenhouse interior containing various cacti and a bright central light fixture. Carefully reconstruct the diagonal structural lines of the glass roof panels and the organic, spiky textures of the foreground succulents to prevent blocking artifacts and checkerboarding that would arise from the sparse sampling patterns in the first measurement channel. Ensure that the high-contrast edges of the central light source are rendered smoothly without ringing artifacts, maintaining color consistency and geometric alignment across both measurement channels. Strictly forbid the model from hallucinating new

objects, introducing artistic stylization, or violating the geometric consistency of the visible roof structure and plant arrangement. Finally, ignore any black padded border regions present in the input during the inference process, but ensure these regions remain solid black in the final reconstructed output.

### M3. tests generation of a single blockwise compressive sensing measurement image from an RGB input.

cs\_block | ratio\_0p031 | sampled 5/33 | seed=0



#### Planner Prompt.


You are an expert in computational imaging, working on the image formation model for compressive sensing. Input: one clean RGB image. Task parameters: - mask family: `{CS_MASK_FAMILY}` - block size: `{CS_BLOCK_SIZE}` - sensing ratio: `{CS_RATIO}` (`{CS_RATIO_TOKEN}`) - target measurement channel: `{CS_MEAS_CHANNEL}` First infer and write the forward model equation, then write an execution prompt for a downstream image editor. Required response format: 1. `FORWARD_MODEL:` - Write the blockwise compressive sensing measurement equation for one channel, for example block extraction, element-wise binary masking, and mask-normalized sum/average. - Instantiate the equation using this sample's parameters (`{CS_MASK_FAMILY}`, block size `{CS_BLOCK_SIZE}`, ratio `{CS_RATIO}`, channel `{CS_MEAS_CHANNEL}`). - State expected output geometry relative to the block size and emphasize that this job produces one single measurement image for `{CS_MEAS_CHANNEL}` only. 2. `EXECUTION_PROMPT:` - Write a strict 4-6 sentence prompt that instructs the image editor to generate exactly one low-resolution measurement image corresponding to `{CS_MEAS_CHANNEL}`. - Enforce faithful blockwise masking-and-aggregation behavior, with no deconvolution/reconstruction, no semantic edits, and no style transfer. - Forbid additive sensor artifacts not implied by the forward model (for example arbitrary blur, interpolation sharpening, hallucinated texture). Hard constraints: - Equation-first ordering is mandatory: `FORWARD_MODEL` must appear before `EXECUTION_PROMPT`. - Output must be a single forward measurement image, not a set of channels. - Treat padded black borders as non-informative during reasoning and keep them black in the output.

#### Additional Ratios (M3).

cs\_block | ratio\_0p047 | sampled 5/27 | seed=0



cs\_block | ratio\_0p062 | sampled 5/31 | seed=0



## Gemini Prompt.

**\*\*FORWARD\_MODEL:\*\*** The blockwise compressive sensing forward model for a specific measurement channel  $m$  is defined by extracting non-overlapping blocks from the image, applying an element-wise binary mask, and computing the normalized sum: 
$$y_{i,j}^{(m)} = \frac{1}{B^2} \sum_{u=0}^{B-1} \sum_{v=0}^{B-1} x_{i,j}(u,v) \cdot \phi_m(u,v)$$
 where  $x_{i,j}$  is the  $(i,j)$ -th image block of size  $B \times B$ ,  $\phi_m$  is the  $m$ -th binary mask from the chosen family, and  $y_{i,j}^{(m)}$  is the resulting scalar measurement for that block. For this specific task: **\*\*Mask Family:\*\*** 'hadamard\_binary\_8x8' **\*\*Block Size (B):\*\*** 8 **\*\*Target Channel (m):\*\*** 'meas\_0' (which corresponds to the first Hadamard basis pattern  $\phi_0$ , an  $8 \times 8$  matrix of all ones). **\*\*Sensing Ratio:\*\*** '0.031' (equivalent to  $K=2$  measurements out of 64, though we are only computing  $m=0$ ). Because the target channel is 'meas\_0' and the first binary Hadamard pattern consists entirely of ones, the operation mathematically simplifies to a local pixel block average. The expected output geometry is a single 2D array (image) of size  $(H/8) \times (W/8)$ , where each pixel contains the normalized measurement value of its corresponding  $8 \times 8$  input block. **\*\*EXECUTION\_PROMPT:\*\*** Generate a single low-resolution measurement image representing the 'meas\_0' channel from an  $8 \times 8$  blockwise compressive sensing forward model. Divide the input image into non-overlapping  $8 \times 8$  blocks and apply the first binary Hadamard pattern, which functions as an all-ones mask. Compute the average value within each masked  $8 \times 8$  block to produce a single pixel in the output matrix, effectively resulting in an 8x downsampled representation of the original image. Output exactly one measurement image corresponding to this first channel, avoiding any stacking of multiple measurements. Do not perform any inverse reconstruction, style transfer, semantic modifications, spatial blurring, or interpolation sharpening.

## OpenAI Prompt.

**FORWARD\_MODEL:** - Let the clean RGB image be  $I \in \mathbb{R}^{\{H \times W \times 3\}}$ . Convert to luminance  $Y = 0.2989 \cdot I_R + 0.5870 \cdot I_G + 0.1140 \cdot I_B$ . - Tile  $Y$  into non-overlapping  $8 \times 8$  blocks  $B_{p,q}$  for  $p=0 \dots H/8-1$ ,  $q=0 \dots W/8-1$ . Treat any padded edges as zeros (remain black). - For mask family hadamard\_binary\_8x8, take the  $8 \times 8$  Hadamard matrix  $H_8$  with entries  $\pm 1$ , binarize via  $M^{(0)} = (H_8 == +1) \cdot \{0,1\}^{\{8 \times 8\}}$ . With sensing ratio 0.031 ( $\sim 2$  of 64), only the first measurement channel meas\_0 is requested, so use mask index 0. - The per-block measurement for meas\_0 is:  $m_{p,q}^{(0)} = (1 / N_1) \cdot \sum_{i=0}^7 \sum_{j=0}^7 B_{p,q}[i,j] \cdot M^{(0)}[i,j]$ , where  $N_1 = \sum_{i,j} M^{(0)}[i,j]$ . - Stack  $m_{p,q}^{(0)}$  into a single measurement image  $M^{(0)} \in \mathbb{R}^{\{H/8 \times W/8\}}$ .


Output geometry equals the block grid (rows =  $H/8$ , cols =  $W/8$ ). This job produces one measurement image for `meas_0` only. EXECUTION\_PROMPT: Generate exactly one grayscale measurement image  $M^{(0)}$  for the input RGB image using the blockwise forward model above. Convert to luminance, partition into  $8 \times 8$  non-overlapping blocks, apply the `hadamard_binary_8x8` mask index 0 to each block, and output the mask-normalized average (sum over ones divided by count of ones) per block as a single pixel in the output grid of size  $H/8 \times W/8$ . Do not attempt any reconstruction, deconvolution, super-resolution, color processing, or semantic editing|only the masking-and-aggregation operation. Do not add blur, sharpening, noise, compression artifacts, or any other sensor effects beyond the stated model. Keep any padded borders black and treat them as non-informative.

### Qwen Prompt.

FORWARD\_MODEL: The forward model partitions the input RGB image  $I$  into non-overlapping blocks of size  $B \times B$  (where  $B=8$ ). For each block  $k$ , a binary mask  $M_k$  is applied, drawn from the `'hadamard_binary_8x8'` family. The sensing ratio  $\rho = 0.031$  implies that approximately  $64 \times 0.031 \approx 2$  pixels per block are active (value 1). The measurement for the target channel `'meas_0'` for block  $k$  is the mask-normalized sum (or average) of the pixel values within that block, defined as:  $Y(u, v) = \frac{1}{\sum_{i,j} M_k(i,j)} \sum_{i=0}^7 \sum_{j=0}^7 M_k(i,j) \cdot I(u \cdot 8 + i, v \cdot 8 + j)$  where  $(u, v)$  are the block coordinates. The expected output geometry is  $(H/8) \times (W/8)$ , producing a single low-resolution measurement image for `'meas_0'` only. EXECUTION\_PROMPT: Generate a single low-resolution measurement image corresponding to channel `'meas_0'` by applying blockwise compressive sensing to the input. Divide the image into non-overlapping  $8 \times 8$  blocks and apply a binary mask from the `'hadamard_binary_8x8'` family with a sensing ratio of 0.031. For each block, compute the measurement value by averaging the pixel intensities where the mask is active. Construct the output image such that each pixel represents one  $8 \times 8$  block measurement, resulting in a downsampled grid. Strictly enforce faithful masking and aggregation behavior with no deconvolution, reconstruction, or style transfer. Do not add arbitrary sensor artifacts like blur or interpolation sharpening, and treat padded black borders as non-informative.

## Lensless Imaging

**M1.** tests reconstruction of a clear scene from a lensless coded measurement and its point-spread function.




### Shared Prompt.

Task: Recover the original 2D scene from this lensless camera measurement. The input is raw sensor data captured using an optical diffuser with a physical aperture placed ~9 mm from a CMOS sensor. Input: A coded-aperture lensless camera measurement, and the point-spread function image. Constraints: - Multiplexing Inversion: Mathematically invert the highly multiplexed, caustic scattering process caused by the optical diffuser. - Artifact Suppression: Suppress the severe background noise, ringing, and cross-talk artifacts typically associated with solving ill-posed non-convex deconvolution problems. - Contrast & Sharpness Recovery: Recover crisp edges and natural contrast from the scattered light field. Maintain the true relative brightness of the light sources and reflective surfaces in the scene. - Pad-Region Handling: If black padded borders are present, treat only the non-black valid region as scene content for reconstruction. Do not let black padded pixels influence structure or tone recovery. - Output Padding Consistency: Keep padded border regions black in the final output at the corresponding locations. - Zero Hallucination: Do not treat the input as an abstract texture to be "stylized." Do not hallucinate recognizable semantic objects (like faces or text) unless they are mathematically supported by the underlying multiplexed signal. Output: A clear, recognizable, and structurally accurate 2D image reconstructed entirely from the scattered lensless measurement and from the point-spread function.

**M2.** tests reconstruction of a clear scene from a lensless coded measurement and its point-spread function.

deconv\_lensless | sampled 5/8 | seed=0



### Planner Prompt.

You are an expert computational imaging assistant. Your task is to analyze a raw sensor measurement captured by a phase-mask or amplitude-mask based lensless imaging system and write a highly specific "execution prompt" for a downstream reconstruction model. Input: A coded-aperture lensless camera measurement. Step 1: Analyze the Measurement Examine the multiplexed sensor data and identify the macroscopic distribution of light|such as the locations of primary bright light sources, high-contrast structural groupings, or overarching gradients. For phase-mask captures, interpret caustic/speckle-like structure; for amplitude-mask captures, interpret broad blur-like or directional (horizontal/vertical) coded patterns. Step 2: Generate the Execution Prompt Write a 4-6 sentence instruction for the image reconstruction model. Use highly descriptive and restrictive keywords. Your generated prompt MUST include: - Explicit identification of the input as a highly multiplexed, lensless measurement that requires structural deconvolution. - Specific identification of the deduced macroscopic light distributions (e.g., "Untangle the heavily multiplexed caustics to recover the two distinct bright light sources dominating the upper left quadrant"). - Explicit handling of black padded borders: ignore padded black areas when inferring scene content, and preserve those padded areas as black in the output. - Strict negative constraints forbidding the model from treating coded measurements (caustic speckle or directional blur patterns) as literal scene texture, and forbidding the hallucination of non-supported semantic objects. Goal: Your generated prompt should act as a perfect algorithmic blueprint, guiding the reconstruction model to mathematically invert the diffuser's scattering process and recover the latent spatial scene.

### Gemini Prompt.

This is a highly multiplexed, lensless measurement from a phase-mask system that requires structural deconvolution. Untangle the heavily multiplexed caustics to recover the prominent, luminous, roughly rectangular object spanning the center horizontally. The input image contains black padded borders; ignore these padded regions when inferring scene content and strictly preserve them as black in the final output. Do not treat the caustic speckle patterns as literal scene texture. Strictly avoid hallucinating any non-supported semantic objects, ensuring the final image is a mathematically faithful inversion of the diffuser's scattering process.

### OpenAI Prompt.


Execution prompt: This is a highly multiplexed, lensless phase-mask/diffuser measurement requiring structural deconvolution of caustic patterns. The active coded region is a roughly square patch offset to the right, surrounded by black padded borders; inside it, energy concentrates along thin bright filaments outlining polygonal cells, with a larger low-intensity void near the center and stronger filaments toward the right and lower edges. Untangle these caustic filaments to recover the minimal set of underlying bright sources/contours that generate the observed intensity, emphasizing the central-right dominance and weaker sources toward the top-left while keeping the background dark. Strictly ignore the padded black areas when inferring scene content and preserve those borders as black in the output. Do not treat the caustic/speckle filaments as literal scene texture and do not hallucinate semantic objects; solve the forward model inversion of the diffuser PSF to produce a spatially regular irradiance map consistent with the multiplexed measurement.

### Qwen Prompt.

This input represents a highly multiplexed, lensless measurement requiring rigorous structural deconvolution to invert the diffuser's scattering process and recover the latent spatial scene. The raw sensor data exhibits a dominant, diffuse yellowish-green light distribution centered in the frame, overlaid with a secondary, high-contrast grid-like mesh structure that indicates a coded aperture pattern. You must untangle these multiplexed signals to distinguish the underlying scene geometry from the coding artifacts, explicitly forbidding the interpretation of the grid lines as literal physical objects like a fence or net. Strictly ignore the extensive black padded borders surrounding the active sensor area when inferring scene content, and preserve these areas as pure black in the output. Do not hallucinate semantic objects unsupported by the diffused light intensity, and resolve the ambiguous, multiplexed textures into a sharp, coherent image.

### M3. tests synthesis of a lensless multiplexed sensor measurement from a clean image and a point-spread function.

deconv\_lensless | sampled 5/86 | seed=0



### Planner Prompt.

You are an expert in computational imaging, working on the image formation model for compressive sensing. Inputs: one clean RGB scene image plus a PSF reference image (see `{INPUT_FILENAMES}`). Task: generate one raw lensless multiplexed

sensor observation. First infer and write the forward model equation, then write an execution prompt for a downstream image editor. Required response format: 1. 'FORWARD\_MODEL:' - Write the image-formation model explicitly. - Describe the multiplexing effect of lensless caustic scattering and how the provided PSF conditions the measurement. - State realistic parameter assumptions (noise level, dynamic range, border handling) without inventing unsupported camera metadata. 2. 'EXECUTION\_PROMPT:' - Write a strict 4-6 sentence prompt that instructs the image editor to generate exactly one unreconstructed multiplexed lensless measurement image. - Enforce heavily scattered, spatially mixed caustic structure consistent with convolution by the supplied PSF. - Forbid standard Gaussian/defocus blur approximations, semantic hallucinations, text overlays, and extra outputs. Hard constraints: - Equation-first ordering is mandatory: 'FORWARD\_MODEL' must appear before 'EXECUTION\_PROMPT'. - Keep this as a forward measurement simulation, not an inverse reconstruction. - If padded borders exist, preserve them as black and do not treat them as valid scene signal.

### Gemini Prompt.

**\*\*FORWARD\_MODEL:\*\*** The forward image-formation model for a linear shift-invariant lensless camera system with a scattering mask (such as a phase diffuser) is mathematically described by the 2D convolution of the scene with the system's Point Spread Function (PSF), subject to sensor noise and dynamic range limits. The equation is: 
$$Y = \text{clip}(\text{Big}(M \odot x) \ast h + \eta, 0, I_{\max})$$
 Where: \*  $Y$  is the raw multiplexed sensor measurement. \*  $x$  is the input scene (the RGB image of the wall sponce). \*  $M$  is a binary spatial mask used to zero out the artificial white padded borders in the provided input, ensuring only the true optical signal is processed. \*  $\odot$  denotes element-wise multiplication (Hadamard product). \*  $h$  is the calibration PSF (the supplied caustic network image). \*  $\ast$  denotes 2D spatial convolution across the spatial dimensions. \*  $\eta \sim \mathcal{N}(0, \sigma^2)$  is an additive Gaussian noise term modeling sensor read and shot noise. \*  $\text{clip}(\cdot, 0, I_{\max})$  enforces the physical dynamic range constraints of the sensor (e.g., clipping to [0, 255] for an 8-bit sensor). **\*\*Multiplexing Effect & PSF Conditioning:\*\*** In a lensless architecture, the physical mask scatters incoming wavefronts rather than focusing them to a point. Every point source in the scene projects a shifted, scaled version of the characteristic caustic network (the PSF) onto the sensor plane. Because the supplied PSF consists of a highly structured, interconnected web of bright caustic lines (resembling Voronoi cells), the resulting measurement  $Y$  will not look like a blurry version of the scene. Instead, it will be a highly multiplexed, tangled superposition of these caustic webs, modulated by the spatial intensity of the glowing wall sponce. **\*\*Parameter Assumptions:\*\*** \* **Noise Level:**  $\sigma \approx 0.02$  (assuming a normalized [0, 1] intensity range) to simulate standard CMOS sensor read noise in low-light conditions. \* **Dynamic Range:** 8-bit simulation; resulting intensities will be strictly clamped between 0 and 255. \* **Border Handling:** The extensive white padding in the source image is treated as non-physical padding ( $M=0$ ); the convolution is computed with zero-boundary conditions, preserving the borders as black in the final sensor measurement. **\*\*EXECUTION\_PROMPT:\*\*** Generate exactly one raw, unreconstructed lensless measurement image by simulating a 2D convolution between the central wall sponce scene and the provided caustic network PSF. First, mathematically isolate the central image by treating the expansive white padded borders as a zero-intensity (black) region, ensuring these bounds do not contribute false light to the convolution and remain strictly black in the final output. Simulate the physical multiplexing effect where the bright hourglass light of the sponce acts as an extended source, projecting heavily overlapping, spatially mixed layers of the web-like caustic structure across the active sensor area. Add subtle Gaussian noise to the resulting signal to mimic real sensor capture and clip the dynamic range to prevent clipping artifacts. Strictly forbid the use of standard Gaussian, defocus, or motion blurs, and do not produce semantic hallucinations, reconstructed scenes, text overlays, or multiple output panels.

### OpenAI Prompt.

**FORWARD\_MODEL:** - Let  $S(x,y,c)$  [0,1] be the clean RGB scene ( $c \in \{R,G,B\}$ ), and let  $h(x,y)$  be the provided single-channel PSF. The raw lensless multiplexed measurement for each color channel is modeled as  $Y_c = \text{clip}(\text{Poisson}(S_c \cdot h) / n_g + n_g, 0, 1)$ , where  $\cdot$  denotes 2D convolution with zero-padding and "same" output size; controls photon count scaling, and  $n_g \sim \mathcal{N}(0, \sigma^2)$  is additive read noise. - **Multiplexing:** in a lensless caustic imager, each scene pixel contributes a shifted copy of the PSF; the sensor records the sum of these overlapping caustic patterns. The supplied PSF conditions the measurement by imposing its bright lobes and dark wedges, producing heavy spatial mixing with high-frequency caustic structure rather than simple blur. - **Assumptions:** dynamic range is linear and clipped to [0,1]; use 4000 peak counts and 0.01 (1% of full scale). Borders are zero-padded (black) and preserved as non-signal. Apply the same PSF to all three channels (or replicate  $h$  for each channel) and do not perform any inverse reconstruction. **EXECUTION\_PROMPT:** - Load `im88.png` as the clean RGB scene and `input_psf.png` as the caustic PSF; convert the PSF to a single-channel kernel and normalize it to unit sum. - Convolve the PSF with each color channel using zero-padding and "same" size, producing a strongly scattered, spatially mixed caustic measurement whose structure matches the supplied PSF, not a Gaussian or defocus blur. - Add Poisson photon noise with a peak equivalent of 4000 counts and Gaussian read noise  $\sigma=0.01$ ; clip the result to the [0,1] range. - Preserve any black padded borders exactly as black and do not introduce semantic content, text, or graphics. - Output exactly one unreconstructed raw lensless multiplexed measurement image.


### Qwen Prompt.

**FORWARD\_MODEL:** The image formation process for this lensless compressive sensing setup is modeled as a linear convolution of the ground truth scene  $x$  with the system's Point Spread Function (PSF)  $h$ , plus additive sensor noise  $n$ . The measurement equation is given by: 
$$y = (x \ast h) + n$$
 where  $\ast$  denotes the 2D convolution operation. In this specific lensless configuration, the PSF  $h$  represents a caustic scattering pattern (as seen in 'input\_psf.png'), which acts as a multiplexing kernel. Instead of a simple blur, each point source in the scene  $x$  is scattered into a complex, spatially varying pattern defined by the PSF, causing information from different spatial locations to overlap and interfere on the sensor plane  $y$ . We assume a low-noise regime with Poisson-Gaussian noise characteristics, a dynamic range mapped to 8-bit integer values (0-255), and zero-padding (black borders) to handle the convolution boundaries without introducing edge artifacts. **EXECUTION\_PROMPT:** Generate a single raw lensless measurement image by convolving the provided scene image with the provided PSF reference. The resulting image must exhibit heavy spatial mixing where every point in the scene is scattered into the specific dual-lobe caustic pattern shown in the PSF, creating a dense, overlapping texture. Avoid simple Gaussian blurs; instead, simulate the diffraction-based multiplexing that creates high-contrast, structured interference patterns across the sensor plane. Preserve the black borders of the input as zero-padded regions and ensure no semantic information is lost to pure noise, but rather mixed into the caustic structure. Output only this single, unreconstructed multiplexed image.

## Longitudinal Chromatic Aberration

**M1.** tests correction of color-dependent blur caused by longitudinal chromatic aberration.

deconv\_longitudinal\_ca | sampled 5/91 | seed=0




### Shared Prompt.

Task: Remove longitudinal chromatic aberration (axial color fringing) from the input image. Input: An image with longitudinal chromatic aberration. Constraints: - Targeted Defringing: Neutralize the false color halos (typically magenta/green or red/blue) surrounding high-contrast edges, backlit subjects, and out-of-focus highlights (bokeh). - Global Color Preservation: Do not globally desaturate the image or alter the overall white balance. The defringing must be strictly localized to the areas experiencing wavelength separation, preserving the true colors of the underlying objects. - Structural & Depth Integrity: Maintain the exact original depth of field, focus roll-off, and image sharpness. Do not artificially blur the edges to hide the fringing, and do not over-sharpen out-of-focus areas. - Zero Hallucination: Do not invent new structural details or alter the shape of the out-of-focus highlights to "fix" the color fringing. Output: A clean, color-accurate image featuring natural edges and pristine out-of-focus regions completely free of optical color separation.

**M2.** tests correction of color-dependent blur caused by longitudinal chromatic aberration.

deconv\_longitudinal\_ca | sampled 5/88 | seed=0



### Planner Prompt.

You are an expert computational imaging assistant. Your task is to analyze an image degraded by longitudinal chromatic aberration (LoCA) and write a highly specific "execution prompt" for a downstream image restoration model. Input: An image with longitudinal chromatic aberration. Step 1: Analyze the Degradation Examine the image to identify where the axial color separation is occurring. Identify the specific colors of the fringing (e.g., magenta fringes on foreground objects, green fringes on the background bokeh) and locate the high-contrast boundaries or highlights most affected by this optical flaw. Step 2: Generate the Execution Prompt Write a 4-6 sentence instruction for the image editing model. Use highly descriptive and restrictive keywords. Your generated prompt MUST include: - Explicit identification of the degradation as longitudinal chromatic aberration or depth-dependent color fringing. - Specific identification of the localized regions and the exact false colors that need neutralizing (e.g., "Neutralize the severe magenta fringing along the foreground tree branches and the green halos in the background bokeh"). - Strict negative constraints forbidding the model from globally desaturating the image, altering the natural color balance, or modifying the image's depth-of-field blur. Goal: Your generated prompt should act as a perfect algorithmic blueprint, guiding the restoration model to neutralize the localized optical false colors without degrading the image's true color palette or spatial focus.

### Gemini Prompt.

The image displays pronounced longitudinal chromatic aberration (LoCA), characterized by distinct depth-dependent color fringing. Neutralize the intense magenta fringing that outlines the foreground elements, specifically the motorcycle's tank, engine block, and the front wheel assembly. Simultaneously, correct the pervasive bright green fringing visible on the out-of-focus background elements, including the chain-link fence, the bridge structure above, and the distant trees. Ensure the correction specifically targets these localized false color artifacts along high-contrast edges and specular highlights. You are strictly forbidden from altering the underlying color palette of the motorcycle (like the tank's hue or the engine's metal tones), applying any global desaturation, or modifying the existing shallow depth-of-field bokeh characteristics.

### OpenAI Prompt.


Step 1 { Degradation analysis: - The image shows longitudinal chromatic aberration: magenta/purple fringes on foreground edges of the motorcycle (headlight rim and glass, fuel-tank contour, handlebars/cables, seat stitching, wheel spokes, and chrome engine highlights). - Green/cyan halos appear in the defocused background, especially along the chain-link fence wires, bridge truss edges, and bright bokeh patches under the bridge. - The most affected zones are high-contrast metallic highlights and dark-light boundaries around the bike and the fence. Step 2 { Execution prompt: Correct longitudinal chromatic aberration (axial, depth-dependent color fringing) across the scene. Neutralize the vivid magenta/purple fringes on the foreground motorcycle|headlight rim/glass edge, fuel-tank upper contour, handlebars/cables, seat stitching, wheel spokes, and chrome engine highlights. Suppress the green/cyan halos in the out-of-focus background|chain-link fence wires, bridge truss edges, and bright bokeh patches beneath the bridge. Apply strictly localized, edge-aware chroma correction; do not globally desaturate, do not alter the natural color balance (retain the warm tan tank paint and neutral metal tones), and avoid introducing halos or sharpening artifacts. Do not modify the depth-of-field or blur characteristics; preserve the current soft background and foreground sharpness while restoring neutral highlights.

**Qwen Prompt.**

The image exhibits severe longitudinal chromatic aberration, characterized by depth-dependent color fringing where out-of-focus planes display shifted color channels. Specifically, neutralize the intense green and cyan halos visible along the high-contrast edges of the foreground motorcycle, particularly around the tires, handlebars, and engine block. Correct the axial color separation in the background by realigning the magenta and green fringes surrounding the out-of-focus bridge structure and chain-link fence bokeh. Ensure that the restoration process strictly preserves the existing depth-of-field blur and does not artificially sharpen the background elements. Avoid globally desaturating the image or shifting the overall color balance, as the goal is only to correct the localized optical fringing without altering the intended vintage purple and green aesthetic.

## Motion Deblurring

M1. tests reconstruction of a sharp image from a motion-blurred observation.




### Shared Prompt.

Task: Remove the motion blur from this image. Deconvolve the blur kernel introduced by camera or subject motion to recover a sharp, clear image. Input: An image with camera or object motion blur. Constraints: - Directional Deblurring: Accurately invert the directional smearing caused by the motion trajectory. Restore crisp edges and fine details that were smeared along the axis of movement. - Artifact Suppression: Avoid introducing ringing artifacts, haloing, or artificial noise amplification, which are common errors when aggressively deconvolving motion blur. - Spatial Consistency: Differentiate between global camera shake (affecting the entire frame) and localized subject motion (affecting only specific objects). Ensure static background elements remain natural and untouched if only the subject is blurred. - Zero Hallucination: Do not invent or hallucinate high-frequency textures (like text, facial features, or intricate patterns) that were completely destroyed by the motion smear. Only restore mathematically recoverable structures. Output: A sharp, well-focused, and artifact-free image where the original motion smear has been completely neutralized.

M2. tests reconstruction of a sharp image from a motion-blurred observation.

deconv\_motion\_blur | sampled 5/94 | seed=0



### Planner Prompt.

You are an expert computational imaging assistant. Your task is to analyze an image degraded by motion blur (characterized by directional smearing and ghosting) and write a highly specific "execution prompt" for a downstream image restoration model. Input: An image with camera or object motion blur. Step 1: Analyze the Degradation Examine the image to identify the nature of the motion blur. Determine the primary direction (angle) and magnitude (length) of the blur smear. Identify whether the blur is caused by global camera shake (affecting everything) or localized subject motion (affecting only a specific object while the background is sharp). Step 2: Generate the Execution Prompt Write a 4-6 sentence instruction for the image editing model. Use highly descriptive and restrictive keywords. Your generated prompt MUST include: - Explicit identification of the degradation as motion blur, specifying whether it is global camera shake or localized subject motion. - Specific identification of the blur's directionality and the critical regions that need targeted deconvolution (e.g., "Remove the horizontal motion smear from the passing car while preserving the already-sharp background"). - Strict negative constraints forbidding the model from adding artificial ringing artifacts, over-sharpening noise, or hallucinating lost structural details like text. Goal: Your generated prompt should act as a perfect algorithmic blueprint, guiding the restoration model to optically invert the specific motion kernel and restore structural sharpness without introducing deconvolution artifacts.

### Gemini Prompt.

**\*\*Step 1: Degradation Analysis\*\*** The image suffers from global camera shake motion blur, affecting all elements equally. The blur exhibits a mild diagonal smear, obscuring the sharp edges of the brick steps, the dry leaf, and the background foliage. **\*\*Step 2: Execution Prompt\*\*** Eliminate the global camera shake motion blur degrading the entire image frame. Precisely deconvolve the diagonal blur kernel targeting the brick stair edges and the dry leaf to restore structural sharpness. Strictly do not introduce ringing artifacts, over-sharpen background noise, or hallucinate lost structural details in the foliage.

### OpenAI Prompt.

Execution prompt: The image suffers from global camera-shake motion blur affecting the entire frame. The smear is predominantly horizontal (approximately 0{5° from the x-axis) with a length of about 8{12 pixels, evident as left-right


ghosting on the stair treads/riser edges and brick joints, as well as the pavilion/building edges in the background. Perform directional deconvolution using a linear motion PSF aligned to this angle and length, prioritizing recovery of crisp edges on the foreground steps and the upper terrace while keeping foliage and structural boundaries natural. Do not introduce ringing halos, double edges, or oversharpened noise, and do not hallucinate fine brick patterns or any nonexistent text. Maintain true geometry, color balance, and perspective during restoration.

### **Qwen Prompt.**

The image is degraded by severe global horizontal motion blur, characterized by uniform directional smearing across the brick stairs, foreground foliage, and background building. Apply a targeted deconvolution process to reverse the horizontal kernel, specifically sharpening the mortar lines and rectangular shapes of the red bricks on the stair treads. Ensure the restoration resolves the edges of the trees and the dark structure in the background without introducing ringing artifacts or artificial halos. Strictly forbid over-sharpening of the noise in the shadowed regions of the stairs and do not hallucinate structural details in the background windows. The goal is a clean inversion of the motion blur that preserves the natural texture of the pavement and leaves.


Spherical Aberration (0.1, 0.15, 0.2, 0.25)

M1. tests correction of blur caused by spherical aberration at a fixed aberration strength.




Additional Strengths (M1).


deconv\_spherical\_aberration | spherical\_0.15 | sampled 5/87 | seed=0



deconv\_spherical\_aberration | spherical\_0.2 | sampled 5/89 | seed=0



deconv\_spherical\_aberration | spherical\_0.25 | sampled 5/89 | seed=0




### Shared Prompt.

Task: Correct the spherical aberration in this image. Remove the blur caused by spherical lens distortion to produce a sharp, well-focused result across the entire field of view. Input: An image with defocus blur caused by spherical aberration. Constraints: - Deblurring & Micro-Contrast: Eliminate the soft "glow" and halos around highlights characteristic of spherical aberration. Restore crisp focus and natural micro-contrast to the underlying structures. - Uniform Sharpness: Ensure the sharpness is recovered consistently across the frame, addressing the radially varying softness without introducing artificial over-sharpening or ringing artifacts. - Highlight Integrity: Recover the core structure of bright objects and light sources that have "bloomed" or washed out due to the optical distortion, without altering the true exposure or clipping the whites. - Zero Hallucination: Do not hallucinate high-frequency textures (like pores, leaves, or fabric grain) that were completely lost to the optical blur. Only restore the mathematically recoverable structures. Output: A crisp, high-contrast, perfectly focused image completely free of the glowing softness and blur associated with spherical lenses.

M2. tests correction of blur caused by spherical aberration at a fixed aberration strength.

deconv\_spherical\_aberration | spherical\_0.1 | sampled 5/90 | seed=0




## Planner Prompt.


You are an expert computational imaging assistant. Your task is to analyze an image degraded by spherical aberration (characterized by a soft, glowing blur and loss of micro-contrast) and write a highly specific "execution prompt" for a downstream image restoration model. Input: An image with defocus blur caused by spherical aberration. Step 1: Analyze the Degradation Examine the image to identify the severity of the spherical blur. Locate specific bright objects, light sources, or high-contrast edges that are suffering from "blooming" or a soft optical glow. Assess the overall loss of micro-contrast across the field of view. Step 2: Generate the Execution Prompt Write a 4-6 sentence instruction for the image editing model. Use highly descriptive and restrictive keywords. Your generated prompt MUST include: - Explicit identification of the degradation as spherical aberration, characterized by soft glowing blur and reduced contrast. - Specific identification of the localized highlights or edges that need targeted glow-removal and sharpening (e.g., "Remove the soft glowing halo around the streetlamps and restore the sharp edges of the surrounding buildings"). - Strict negative constraints forbidding the model from using generic, aggressive sharpening filters that cause ringing artifacts, and forbidding the hallucination of lost textures. Goal: Your generated prompt should act as a perfect algorithmic blueprint, guiding the restoration model to optically invert the glowing blur and restore structural sharpness without introducing artificial edge enhancement.

## Additional Strengths (M2).


deconv\_spherical\_aberration | spherical\_0.15 | sampled 5/87 | seed=0



deconv\_spherical\_aberration | spherical\_0.2 | sampled 5/89 | seed=0



deconv\_spherical\_aberration | spherical\_0.25 | sampled 5/90 | seed=0



### Gemini Prompt.

This image displays significant defocus blur consistent with spherical aberration, leading to a soft, glowing appearance and a noticeable loss of micro-contrast, particularly evident in the fine details of the wood grain and the edges of the drilled holes. The bright highlights on the wood surfaces exhibit a subtle blooming effect. To correct this, apply a deconvolution filter specifically calibrated for spherical aberration to invert the soft, glowing blur and restore the lost micro-contrast across the image. Target the blooming highlights on the cut ends of the wood and the edges of the drilled holes, reducing the localized glow and restoring their crisp definition. Do not use generic unsharp mask or high-pass filters, as these will introduce ringing artifacts along the high-contrast edges. Strictly avoid hallucinating fine wood textures or adding artificial grain; the restoration must focus purely on recovering the underlying structural sharpness obscured by the optical aberration.

### OpenAI Prompt.

The image is degraded by spherical aberration, producing a soft glowing blur and reduced micro-contrast across the frame. Perform optical deconvolution to remove the glow and recover edge acuity, targeting the sunlit rims of the drilled holes in the wooden logs, the perforation edges of the red brick, the thin wire-mesh grid lines, and the cut-wood boundaries where blooming halos are visible. Restore fine micro-contrast in wood grain and brick texture while keeping natural luminance and color; suppress the veiling flare without adding halos. Do not use generic, aggressive sharpening filters, unsharp mask, or edge-overshoot methods that create ringing or halos. Do not invent or hallucinate textures; reconstruct only structure implied by the existing signal and preserve the original noise characteristics.


### Qwen Prompt.

Correct the image degradation caused by spherical aberration, characterized by a pervasive soft glowing blur and a significant loss of micro-contrast across the wood and brick textures. Target the bright, high-contrast edges of the drilled log holes and the perimeter of the wooden shelf dividers to remove the specific luminous halos that are causing the 'mushy' appearance and loss of definition. Apply a precise deconvolution filter that restores the sharpness of the bark grain and the brick perforations while strictly forbidding the use of aggressive sharpening kernels that generate

ringing artifacts. Ensure the model does not hallucinate lost details in the dark, low-contrast areas, preserving the natural, organic look of the insect habitat without creating artificial, hard edges.

## Demosaicking (Hexadeca)

M1. tests full-color image reconstruction from a sparse hexadeca sampling pattern.




### Shared Prompt.

Task: Demosaic this hexa-deca RGG B Bayer pattern image. Reconstruct the full-color RGB image from the raw sensor data captured with a 4x4 hexa-deca RGG B color filter array. Input: A hexadeca (8x8 super-pixel) Bayer mosaic image. Sensor Layout: Each pixel records only one color channel. The 8x8 repeating super-pixel tile is arranged as: R R R R G G G G R R R R G G R R R R G G G G R R R R G G G G G G B B B B G G G G B B B B G G G G B B B B G G G G B B B B Each 4x4 block of identical color values forms a "hexa-deca" sub-pixel. Your task is to reconstruct the two missing color channels at every pixel position from this very coarsely sampled color mosaic. Constraints: - Macro-Block Handling: Effectively interpolate across the large 4x4 homogeneous RGG B color blocks without introducing blocky artifacts or severe false colors at object boundaries. - Artifact Suppression: Strictly minimize aliasing and severe color fringing, which are highly prone in 4x4 arrays. - Spatial Resolution Recovery: Reconstruct fine spatial details while preserving natural gradients. Avoid artificial smoothing or painterly textures often caused by aggressive interpolation. - Zero Hallucination: Do not invent structural details or hallucinate textures to fill gaps between color samples. Output: A pristine, full-color RGB image reconstructed faithfully from the 4x4 hexa-deca RGG B Bayer array.

M2. tests full-color image reconstruction from a sparse hexadeca sampling pattern.

demaosaicking\_hexadeca | hexadeca | sampled 5/74 | seed=0



**Planner Prompt.**

You are an expert computational imaging assistant. Your task is to analyze a raw sensor image captured with a 4x4 Hexadeca RGB Bayer color filter array (CFA) and write a highly specific "execution prompt" for a downstream demosaicking model. Input: A hexadeca (8x8 super-pixel) Bayer mosaic image. The sensor's 8x8 repeating super-pixel tile is arranged as: R R R R G G G G R R R R G G G G R R R R G G G G R R R R G G G G G G G G B B B B G G G G B B B B G G G G B B B B G G G G B B B B. Each 4x4 block of identical color values forms a "hexa-deca" sub-pixel. Two of the three RGB channels are missing at every pixel location. Step 1: Analyze the Image Scan the Hexadeca RGB Bayer mosaiced image. Because of the large 4x4 homogeneous color blocks, identify object boundaries, fine lines, and high-contrast transitions that are highly prone to severe color fringing and blocky interpolation artifacts. Step 2: Generate the Execution Prompt Write a 4-6 sentence instruction for the image editing model. Use highly descriptive and restrictive keywords. Your generated prompt MUST include: - Explicit identification that the input is a 4x4 Hexadeca RGB Bayer pattern with the pixel layout described above. - Specific identification of the regions or boundary edges in the image that require careful macro-block interpolation to prevent color fringing (e.g., "Ensure smooth boundary transitions around the tree branches without blocky color bleeding"). - Strict negative constraints forbidding the model from blurring edges, generating false colors, or hallucinating artificial textures to fill the large sampling gaps. Goal: Your generated prompt should act as a perfect algorithmic blueprint, guiding the editing model to smoothly resolve the 4x4 macro-blocks without introducing severe perceptual or color errors.

**Gemini Prompt.**

This input is a raw sensor image encoded with a 4x4 Hexadeca RGB Bayer color filter array, characterized by an 8x8 repeating super-pixel tile containing 4x4 homogeneous macro-blocks (RRRR/GGGG top, GGGGBBBB bottom). Execute a high-fidelity demosaicking process optimized for large macro-block spatial sampling to reconstruct the full-color image. It is critical to apply advanced edge-directed interpolation around the complex, overlapping network of fine tree branches against the bright sky and the high-contrast painted lines curving along the road, ensuring smooth boundary transitions without introducing blocky color bleeding or zipper artifacts. Strictly preserve the sharpness of the structural edges, including the tree trunks and pavement cracks, without resorting to low-pass blurring. The model is expressly forbidden

from generating false chromatic aliases, localized color fringing, or hallucinating artificial foliage or road textures to fill the severe informational gaps left by the missing color channels.

### **OpenAI Prompt.**


Input is a 4x4 Hexadeca RGGB Bayer CFA with an 8x8 repeating super-pixel arranged exactly as: R R R R G G G G / R R R R G G G G / R R R R G G G G / R R R R G G G G / G G G G B B B B / G G G G B B B B / G G G G B B B B / G G G G B B B B; two color channels are missing at every pixel. Perform macro-block-aware, edge-directed interpolation, giving special care to high-contrast boundaries: the thin tree branches against the bright sky, the road edges and center double lines, fence posts/wires, shrub outlines, pavement crack edges, and the distant horizon. Ensure smooth boundary transitions in these areas without blocky color bleeding; use green-channel gradient guidance and cross-channel color-ratio consistency to choose interpolation direction across 4x4 blocks. Fill missing channels with directional interpolation and deblocking only within uniform regions (open sky and flat asphalt), never across detected edges or fine lines. Strict constraints: do not blur edges, do not generate false colors, do not hallucinate textures or grain to fill the large sampling gaps; avoid zippering, ringing, checkerboard artifacts, and preserve true luminance structure and natural chroma.

### **Qwen Prompt.**

Process the provided raw sensor image which utilizes a non-standard 4x4 Hexadeca RGGB Bayer color filter array, characterized by large 4x4 homogeneous sub-pixels arranged in quadrants (Red, Green, Green, Blue) within an 8x8 repeating super-pixel tile. Focus your demosaicking algorithm on the high-frequency details of the deciduous trees on the left and the thin, intricate branches against the bright sky, as these regions are most susceptible to visible macro-block grid patterns. Strictly avoid "blocky" interpolation artifacts where color values jump abruptly between the 4x4 color blocks, ensuring smooth boundary transitions around the tree limbs to prevent severe color fringing where dark branches meet the background. Do not apply aggressive smoothing that would blur the texture of the cracked asphalt road or hallucinate false colors in the sky to fill the large sampling gaps.

## Demosaicking (Quad)

M1. tests full-color image reconstruction from a quad Bayer sampling pattern.




### Shared Prompt.

Task: Demosaic this quad RGGB Bayer pattern image. Reconstruct the full-color RGB image from the raw sensor data captured with a 2x2 quad RGGB Bayer color filter array. Input: A quad (4x4 super-pixel) Bayer mosaic image. Sensor Layout: Each pixel records only one color channel. The 4x4 repeating super-pixel tile is arranged as: R R G G R R G G G B B G G B B. Each 2x2 block of identical color values forms a "quad" sub-pixel. Your task is to reconstruct the two missing color channels at every pixel position from this sparse color mosaic. Constraints: - Artifact Suppression: Minimize aliasing, moiré patterns, and "zippering" artifacts along high-frequency edges. - Spatial Resolution Recovery: Accurately reconstruct fine spatial details without artificially blurring or over-sharpening the image. - Color Fidelity: Prevent false color generation in areas of high-contrast texture. Ensure that the reconstructed RGB values perfectly map to the original scene's luminance and chrominance. - Zero Hallucination: Do not invent structural details that are not present in the raw subsampled pixel data. Output: A pristine, full-color RGB image reconstructed faithfully from the 2x2 quad RGGB Bayer array.

M2. tests full-color image reconstruction from a quad Bayer sampling pattern.

demaicking\_quad | quad | sampled 5/81 | seed=0



### Planner Prompt.

You are an expert computational imaging assistant. Your task is to analyze a raw sensor image captured with a 2x2 Quad RGGB Bayer color filter array (CFA) and write a highly specific "execution prompt" for a downstream demosaicking model. Input: A quad (4x4 super-pixel) Bayer mosaiced image. The sensor's 4x4 repeating super-pixel tile is arranged as: R R G G R R G G G G B B G G B B Each 2x2 block of identical color values forms a "quad" sub-pixel. Two of the three RGB channels are missing at every pixel location. Step 1: Analyze the Image Scan the Quad RGGB Bayer mosaiced image for high-frequency structural details (like thin lines, grids, or dense foliage) that are highly susceptible to aliasing, moiré, and false coloring during the 2x2 interpolation process. Step 2: Generate the Execution Prompt Write a 4-6 sentence instruction for the image editing model. Use highly descriptive and restrictive keywords. Your generated prompt MUST include: - Explicit identification that the input is a 2x2 Quad RGGB Bayer pattern with the pixel layout described above. - Specific identification of the regions or textures in the image that require careful artifact suppression (e.g., "Pay special attention to the striped shirt to prevent moiré"). - Strict negative constraints forbidding the model from blurring edges, generating false colors, or hallucinating artificial textures. Goal: Your generated prompt should act as a perfect algorithmic blueprint, guiding the editing model to cleanly interpolate the missing RGB channels without introducing perceptual errors.

### Gemini Prompt.

This input is a 2x2 Quad RGGB Bayer mosaiced image. Reconstruct the full-color image by applying a high-quality demosaicking algorithm designed specifically for the Quad Bayer layout (R R G G / R R G G / G G B B / G G B B). Pay special attention to the brick wall background and the vertical and horizontal mortar lines, as these repetitive grid-like structures are highly susceptible to severe moiré and zipping artifacts during the 2x2 interpolation. Ensure sharp, artifact-free reconstruction of the fine details on the saxophone and the subject's suit jacket. Strictly avoid blurring the structural edges, introducing false colors along the brick mortar, or hallucinating artificial textures within the dense grid patterns. Maintain structural integrity and color accuracy throughout the interpolation process.

### OpenAI Prompt.


Input is a 2x2 Quad RGGB Bayer mosaic with a 4x4 repeating tile: R R G G / R R G G / G G B B / G G B B; reconstruct the two missing channels at every pixel respecting this quad layout. Use edge-aware, directionally selective interpolation within and across quads to prevent zippering and stair-stepping. Pay special attention to the brick wall's dense horizontal/vertical grout grid, which is highly prone to aliasing, moiré, and false color; preserve sharp brick edges while suppressing rainbowing. Also handle the saxophone's shiny metal keys, mouthpiece, and narrow contours, plus jacket seams, to avoid color fringing and ringing near specular highlights and fine lines. Do not blur edges, do not introduce false colors, and do not hallucinate textures or patterns; maintain channel consistency and natural luminance throughout.

### **Qwen Prompt.**

Execute demosaicking on this raw sensor data configured as a 2x2 Quad RGGB Bayer pattern, strictly adhering to the provided 4x4 repeating super-pixel tile layout where 2x2 blocks of identical colors are arranged (R R G G / R R G G / G G B B / G G B B). Focus heavily on the high-frequency texture of the brick wall background, interpolating the repeating mortar lines and brick edges to prevent severe moiré artifacts and false coloring that typically arise from this specific sampling grid. Simultaneously, reconstruct the fine metallic details of the saxophone keys and the smooth gradients of the musician's face and suit without introducing "zippering" or jagged edges along high-contrast boundaries. Apply edge-preserving interpolation to maintain the sharp definition of the suit fabric and individual bricks, strictly forbidding global blurring that would obscure these textures. Finally, ensure the output is free of artificial halos, false colors, or hallucinated textures, particularly in the shadowed areas beneath the saxophone and the dark clothing.

## Demaicking (Regular)

M1. tests full-color image reconstruction from a regular Bayer sampling pattern.




### Shared Prompt.

Task: Demosaic this regular RGG B Bayer pattern image. Reconstruct the full-color RGB image from the raw sensor mosaic.  
 Input: A regular Bayer mosaic image. Sensor Layout: The repeating 2x2 Bayer tile is: R G G B Constraints: - Color fidelity: Reconstruct missing channels while preserving natural color relationships and avoiding false-color artifacts. - Edge-aware interpolation: Keep high-contrast edges sharp and suppress zippering or moire artifacts on fine repetitive textures. - Detail preservation: Recover fine spatial detail without excessive smoothing or synthetic over-sharpening. - Zero hallucination: Do not invent structures or textures not supported by the sampled mosaic. Output: A clean, full-color RGB image faithfully reconstructed from the regular RGG B Bayer input.

M2. tests full-color image reconstruction from a regular Bayer sampling pattern.

demaicing\_regular | regular | sampled 5/91 | seed=0



### Planner Prompt.

You are an expert computational imaging assistant. Your task is to analyze a raw sensor image captured with a regular 2x2 RGB Bayer color filter array (CFA) and write a highly specific "execution prompt" for a downstream demosaicking model. Input: A regular Bayer mosaic image. The sensor's repeating 2x2 tile is: R G G B Step 1: Analyze the Image Scan the mosaiced input and identify high-frequency edges, thin structures, and repetitive textures that are most vulnerable to zipping, moire, and false-color artifacts during interpolation. Step 2: Generate the Execution Prompt Write a 4-6 sentence instruction for the image model. Use highly descriptive and restrictive keywords. Your generated prompt MUST include: - Explicit identification that the input is a regular 2x2 RGGG Bayer mosaic. - Specific guidance for edge-aware reconstruction in regions prone to color artifacts. - Strict negative constraints forbidding edge blur, false colors, and hallucinated textures. Goal: Your generated prompt should act as a precise demosaicking blueprint that recovers accurate RGB detail from the regular Bayer sampling pattern.

### Gemini Prompt.

### Image Analysis The input image contains dense, wet bear fur and turbulent water. These high-frequency, intersecting structural lines and repetitive textures are highly susceptible to zipping, moiré, and false-color artifacts during interpolation. ### Execution Prompt Reconstruct a full-color RGB image from this raw sensor input, which utilizes a standard 2x2 RGGG Bayer color filter array. Employ strict directional, edge-aware interpolation to accurately resolve the high-frequency textures of the wet, matted bear fur and sharp water splashes. Utilize cross-channel correlation to maintain precise structural boundaries where the high-contrast fur meets the water. Strictly forbid the introduction of false colors, chromatic aliasing, or moiré patterns within the repetitive fur details. Finally, ensure zero zipping along sharp edges and entirely prohibit edge blurring or hallucinated textures in the final output.

### OpenAI Prompt.

Step 1 { Image analysis: - The scene contains very fine, wet bear fur with dense, repetitive strands that are highly susceptible to zipping and moire if interpolated across the grain. - Sharp, high-contrast edges occur at the open mouth, teeth, nose, and ear outlines; these regions are prone to color fringing and edge blurring. - Water ripples and small specular highlights on the wet fur introduce repetitive high-frequency textures that can trigger false-color ringing. -


Overlapping limbs and muzzle transitions form thin structures and curved boundaries that require directional interpolation. Step 2 { Execution prompt for the demosaicking model: - The input is a regular 2x2 RGGB Bayer mosaic (tile: R G / G B). Perform edge-aware, directional interpolation using the green channel as the luminance anchor; estimate local gradient orientation and interpolate along fur strands and water ripple directions, not across strong edges. - Reconstruct red/blue chroma by enforcing cross-channel consistency: minimize chroma variation across detected luminance edges, keep chroma smooth where luminance is smooth, and maintain neutral highlights on teeth and specular wet areas. - Suppress zippering around thin fur, ear contours, and mouth boundaries with gradient-corrected interpolation and limited chroma-domain regularization (Laplacian or TV) without smoothing luminance detail. - Hard constraints: no edge blur, no false colors, no moire, no halos, and no hallucinated textures; preserve true RGB detail and accurate edge positions derived from the RGGB sampling pattern.

### **Qwen Prompt.**

**\*\*Step 1: Analyze the Image\*\*** The input image displays a scene of two bears interacting in water, characterized by extremely high-frequency textures in the wet fur and chaotic, high-contrast edges in the splashing water. The repetitive, noisy texture of the fur is particularly vulnerable to "zippering" artifacts if the demosaicking algorithm fails to follow the local luminance gradients accurately. Furthermore, the thin, high-contrast structures of the bear's open mouth and teeth



denoising | SIDD\_1024 | sampled 5/98 | seed=0



### Planner Prompt.

You are an expert computational imaging assistant. Your task is to analyze a degraded, noisy image and write a highly specific "execution prompt" for a downstream image-to-image diffusion model. Input: A noisy image from a smartphone camera. Step 1: Analyze the Image Identify the specific nature of the noise (e.g., color-channel salt-and-pepper noise, low-light sensor grain, compression artifacts, or luminance streaks). Identify the critical textures that must be saved (e.g., skin pores, fabric weave, architectural detail). Step 2: Generate the Execution Prompt Write a 4-6 sentence instruction for the image editing model. Use highly descriptive, aesthetic, and restrictive keywords. Your generated prompt MUST include: 1. A description of the specific noise to be removed. 2. A list of specific "anchor textures" in this image that must remain untouched. 3. Strict negative constraints to prevent the model from adding new content or changing colors. Goal: Your generated prompt should allow the editing model to act as a perfect inverse solver for this specific image's noise profile.

### Gemini Prompt.

Denoise this image by removing the pervasive, fine-grained sensor noise and chrominance speckling, characteristic of low-light smartphone photography. Crucially, preserve the subtle, woven texture present in the upper background region. Maintain the sharp, distinct edges of the colored squares and the precise geometric grid structure without any softening or blurring. Strictly avoid introducing any new details, textures, or patterns into the image. Ensure the original color palette, saturation, and luminance distribution of all elements remain absolutely unchanged.

### OpenAI Prompt.

**Step 1 | Image analysis** - **Noise type:** Heavy **low-light smartphone sensor noise**, dominated by fine **luminance grain** and dense **RGB chroma speckling/mottling** across the entire frame, strongest in the dark black bars and the flat midtone color panels. It does **not** read as salt-and-pepper noise; it is more like high-ISO color blotchy grain with slight coarse shadow noise. - **Anchor textures to preserve:** the **subtle plaster/concrete-like surface texture** in the large gray upper region, the **crisp straight horizontal and vertical black divider bars**, the **hard-edged rectangular geometry**, and the **matte, flat color fields** in the muted lavender, olive-brown, mauve-purple, dusty pink, and yellow-green blocks. **Step 2 | Execution prompt** Remove only the **dense high-ISO low-light smartphone sensor noise**:


fine luminance grain plus multicolored RGB chroma speckle/blotchy mottling spread over the whole image, especially inside the dark divider bars and the flat colored rectangles. Preserve these anchor textures exactly: the **\*\*faint plaster/concrete texture\*\*** in the large gray upper panel, the **\*\*razor-straight black grid bars\*\***, the **\*\*hard geometric edges\*\*** of every rectangle, and the **\*\*matte uniform fills\*\*** of the muted lavender, olive-brown, mauve, dusty pink, and yellow-green regions. Apply precise denoising only, keeping all boundaries, alignment, proportions, and tonal separations unchanged, and do not over-smooth the intentional surface texture in the gray area. **\*\*Do not add new detail, patterns, gradients, reflections, shadows, brush texture, or sharpening halos; do not repaint or reinterpret any region.\*\*** **\*\*Absolutely no color drift\*\***: no hue shift, no saturation change, no white-balance correction, no contrast restyling, no cropping, no warping, and no geometry alteration|produce the same image as a clean inverse of its current noise profile.

**Qwen Prompt.**

1. Remove the pervasive, high-ISO chromatic noise and fine luminance grain that creates a speckled, static-like overlay across the entire image, particularly obscuring the details in the upper grey region. 2. Preserve the subtle, rough texture of the grey upper section and the sharp, non-reflective finish of the thick black grid lines separating the colored blocks. 3. Ensure the solid color fields (blue, olive, purple, red, dark violet, yellow) are smoothed of their heavy speckle while maintaining their original matte, paper-like saturation and flat appearance. 4. Strictly forbid the model from adding new details, shifting hues, or blurring the crisp boundaries between the grid cells to prevent a "plastic" or over-smoothed look. 5. The result should be a clean, flatbed-scan quality image that restores clarity and color fidelity without losing the physical texture of the original medium.

**M3. tests realistic smartphone noise synthesis from a clean reference image.**

denoising | SIDD\_1024 | sampled 5/97 | seed=0



**Planner Prompt.**

You are an expert in computational imaging, working on the image formation model for compressive sensing. Input: one clean smartphone image. Per-image metadata parsed from filename: - scene instance: '{SCENE\_INSTANCE\_NUMBER}' - scene number:

{SCENE\_NUMBER} - camera: {CAMERA\_CODE} ({CAMERA\_NAME}) - ISO: {ISO\_LEVEL} - shutter code: {SHUTTER\_SPEED\_CODE} (approx exposure {SHUTTER\_EXPOSURE\_SECONDS}) - illuminant temperature: {ILLUMINANT\_TEMPERATURE\_K} K - brightness condition: {ILLUMINANT\_BRIGHTNESS\_CODE} ({ILLUMINANT\_BRIGHTNESS\_LABEL}) First infer and write the forward model equation, then write an execution prompt for a downstream image editor. Required response format: 1. 'FORWARD\_MODEL:' - Write a smartphone noise image-formation model with parameter discussion grounded in the provided metadata. - Explain how ISO, exposure proxy, illuminant, and brightness condition should modulate noise level/chromaticity. - Keep the model realistic for generic mobile camera noise, not synthetic artistic grain. 2. 'EXECUTION\_PROMPT:' - Write a strict 4-6 sentence prompt that instructs the image editor to generate exactly one noisy image from the clean input. - Require preservation of scene geometry and color identity while injecting plausible smartphone sensor noise. - Forbid blur-based degradation, content hallucination, color cast drift unrelated to metadata, text overlays, and extra outputs. Hard constraints: - Equation-first ordering is mandatory: 'FORWARD\_MODEL' must appear before 'EXECUTION\_PROMPT'. - This is forward noise synthesis (clean -> noisy), not denoising. - Keep padded black regions black if present.

### Gemini Prompt.

\*\*FORWARD\_MODEL:\*\* The noise synthesis follows a heteroscedastic (signal-dependent) image formation model to approximate the sensor noise characteristics of a Google Pixel smartphone before heavy multi-frame denoising. The observed noisy pixel intensity  $Y_{c,c}$  for a given color channel  $c \in \{R, G, B\}$  is modeled as the clean signal  $X_{c,c}$  corrupted by additive noise  $N_{c,c}$ :  $Y_{c,c} = X_{c,c} + N_{c,c}$ .  $N_{c,c}$  is the total variance at signal level  $X_{c,c}$ .  $\sigma_{read}^2(X_{c,c}) = K \cdot X_{c,c} + \sigma_{read}^2$  models the Poisson-distributed photon shot noise, approximated here as a Gaussian variance proportional to the signal. The parameter  $K$  represents overall system gain.  $\sigma_{read}^2$  models the signal-independent Gaussian read noise from the sensor electronics. \*\*Parameter Discussion driven by Metadata:\*\* \* \*\*ISO (00800) & Brightness (Low Light):\*\* An ISO of 800 on a small mobile sensor indicates significant analog and digital gain ( $K$  is large) applied to compensate for the 'L' (low light) condition. This will dramatically inflate both the read noise variance ( $\sigma_{read}^2$ ) and the shot noise component, resulting in a low Signal-to-Noise Ratio (SNR). The noise will be highly visible, particularly in the darker patches of the color checker where read noise dominates. \* \*\*Shutter Code (00640 / 1/640s):\*\* This is a relatively fast shutter speed for a low-light environment. A short integration time means very few photons are collected (low  $X_{c,c}$ ), forcing reliance on the high ISO gain and exacerbating the dominance of sensor noise over the actual light signal. \* \*\*Illuminant Temperature (5500 K):\*\* A 5500K illuminant represents standard daylight or electronic flash, which is relatively neutral. Because the physical illuminant is balanced, the camera's Image Signal Processor (ISP) does not need to apply extreme, asymmetric digital white balance gains to the Red or Blue channels. Consequently, the noise spectrum should remain relatively balanced across the RGB channels, avoiding the heavy blue-channel chroma noise typically seen under tungsten (incandescent) lighting. \*\*EXECUTION\_PROMPT:\*\* Generate exactly one noisy image from the provided clean input by simulating the sensor noise profile of a Google Pixel camera operating at ISO 800 with a 1/640s shutter speed in low light. Apply a signal-dependent heteroscedastic noise model where overall variance is strongly amplified by the high ISO, creating prominent luminance grain and subtle low-frequency chroma noise. Because the illuminant is a neutral 5500K, distribute the noise relatively evenly across the RGB channels without extreme asymmetric color channel amplification. The noise must be most pronounced in the darker, signal-starved regions of the color checker, accurately reflecting real-world photon and read noise limits. Strictly maintain the original image geometry, sharp structural borders, and underlying color identity; do not introduce blur, structural hallucinations, or text overlays. Finally, if the image contains any completely unexposed padded black border regions, they must remain absolutely pure black (RGB 0,0,0) with zero noise injected.

### OpenAI Prompt.


FORWARD\_MODEL: - Let  $x_{srgb}$  be the clean image. Convert to linear RGB,  $x = [-1](x_{srgb})$ . The noisy image is produced by a Poisson(Gaussian sensor model with gain and fixed-pattern terms:  $y_{lin} = clip(m(g \cdot x) + \text{shot}(x, g, t) + \text{read}(g, L) + b_{rowcol}(g, L))$ ,  $y = (y_{lin})$ . Where  $g = ISO/ISO0$  with  $ISO0=100$  (here  $g8$ ),  $t$  is exposure (1/640 s),  $m=1$  is PRNU ( $N(0, prnu^2)$ ),  $\text{shot}_c \sim N(0, g^2 \cdot c \cdot t \cdot x_c)$  is signal-dependent shot noise per channel  $c$ ,  $\text{read}_c \sim N(0, c \cdot g^2 \cdot f_L)$  is signal-independent read/dark noise, and  $b_{rowcol}$  adds weak row/column banding.  $_c$  encodes channel photon efficiency under the illuminant; for 5500 K daylight on a GP RGGG sensor,  $_G1, _R0.9, _B0.8$  so blue is slightly noisier. Low-light condition  $L$  increases  $f_L > 1$  (e.g., 1.5(2x) and modest banding. The short exposure (1/640 s) lowers photon counts, boosting the relative shot noise; ISO 800 raises both shot and read noise after analog gain. Keep padded black regions at zero (no offset) so blacks remain black; apply only mild JPEG quantization if desired, without changing color balance. EXECUTION\_PROMPT: - Generate exactly one noisy version of the input image consistent with a Google Pixel shot at ISO 800, 1/640 s in low light under a 5500 K illuminant. - Work in linear RGB and inject Poisson(Gaussian noise: signal-dependent shot noise scaled by the gain (~8x) and short exposure, plus signal-independent read/dark noise with slightly stronger variance in the blue channel; add subtle PRNU and faint row/column banding. - Preserve scene geometry, edges, and all object colors; the mean color/white balance should remain unchanged and any padded black areas must stay black. - Do not introduce blur, sharpening, hallucinated content, text/graphics overlays, or color casts unrelated to the metadata. - Return a single image at the original resolution that exhibits realistic smartphone noise appropriate for low-light ISO 800 conditions.

### Qwen Prompt.

FORWARD\_MODEL: The image formation model for a smartphone sensor in low-light conditions is approximated by a signal-dependent noise process followed by amplification and quantization. Let  $X$  denote the clean linear radiance image. The noisy output  $Y$  is modeled as:  $Y = \mathcal{Q} \left( G_{ISO} \cdot \left( \mathcal{P} \left( \frac{X}{G_{ISO}} \right) + \mathcal{N} \left( 0, \sigma_{read}^2 \right) \right) \right)$  where  $\mathcal{P}$  represents Poisson-distributed photon shot noise and  $\mathcal{N}$  represents Gaussian read noise. The parameter  $G_{ISO}$  corresponds to the amplification factor for ISO 800, which significantly elevates the visibility of  $\sigma_{read}$  (read noise). The shutter time (1/640 s) limits photon integration, reducing the mean signal intensity and thereby increasing the relative variance of the shot noise component  $\mathcal{P}$ . The illuminant temperature (5500 K) establishes the white balance baseline, ensuring noise chromaticity remains largely neutral but potentially exhibiting higher variance in the blue channel typical of low-light sensor performance. The brightness condition 'L' confirms that the input signal  $X$  resides in a low-intensity regime, making the additive noise term dominant and resulting in a grainy texture characteristic of high-ISO mobile photography. EXECUTION\_PROMPT: Generate a single noisy image derived from the provided clean input of a color calibration chart. Apply a realistic smartphone noise texture consistent with high ISO (800) and low-light conditions, ensuring the grain is visible across both the colored squares and the background texture. Strictly preserve the sharp geometric boundaries of the black frame and the distinct color identities of the patches (blue, green, purple, red) without introducing blur or distortion. Do not hallucinate new content, add text overlays, or drift the color cast significantly away from the 5500K daylight baseline. Ensure that any padded black regions remain solid black and that the overall composition remains faithful to the original scene geometry.

## Event-Based Reconstruction

M1. tests intensity-image reconstruction from event-camera measurements.




## Shared Prompt.

Task: Reconstruct an intensity image from a single event representation. Input: One event image `{PRIMARY_IMAGE_FILENAME}`, whose filename suffix indicates temporal accumulation scale (`*_16.png`, `*_32.png`, or `*_full.png`). Suffix interpretation: `_16` = short accumulation window, `_32` = medium accumulation window, `_full` = full accumulation window. For this sample, use accumulation scale `{EVENT_ACCUMULATION_SCALE}`. Event encoding note: - The event image is accumulated from events  $(x, y, t, p)$  over the selected window. - Polarity  $p=1$  (ON) means local brightness increased;  $p=0$  (OFF) means local brightness decreased. - Per pixel, ON contributes  $+1$  and OFF contributes  $-1$ , then values are rendered around a neutral gray baseline `128`. - Pixels above `128` indicate ON-dominant activity; pixels below `128` indicate OFF-dominant activity. - This input encodes brightness change dynamics, not absolute scene intensity. Constraints: - Scale awareness: Respect the input accumulation scale (16, 32, or full) and reconstruct the corresponding intensity frame for that same scale. - Edge and texture fidelity: Preserve fine contours and high-frequency details while suppressing event noise and sparsity artifacts. - Photometric plausibility: Produce a natural-looking intensity image without artificial over-sharpening, checkerboard artifacts, or contrast exaggeration. - Zero hallucination: Do not invent objects or scene structures not supported by the provided event input. Output: A clean, structurally accurate intensity image reconstructed from the provided event input.

M2. tests intensity-image reconstruction from event-camera measurements.

event | sampled 5/93 | seed=0



### Planner Prompt.

You are an expert computational imaging assistant. Your task is to analyze a single event representation and write a highly specific "execution prompt" for a downstream event-to-image reconstruction model. Input: One event image `{PRIMARY_IMAGE_FILENAME}` with suffix `*_16`, `*_32`, or `*_full` indicating temporal accumulation scale. Suffix interpretation: `_16` = short accumulation window, `_32` = medium accumulation window, `_full` = full accumulation window. For this sample, the scale is `{EVENT_ACCUMULATION_SCALE}`. Event encoding note: - The input is built from events `(x, y, t, p)` accumulated over the selected window. - `p=1` (ON) indicates local brightening; `p=0` (OFF) indicates local darkening. - ON/OFF events are summed as signed counts per pixel (`+1` / `-1`) and rendered around baseline gray `128`. - Values above/below `128` represent ON-dominant/OFF-dominant change respectively. - The representation encodes temporal brightness change, not direct intensity. Step 1: Analyze the Event Evidence Use the provided suffix-derived scale `{EVENT_ACCUMULATION_SCALE}`, then inspect reliable edges, motion traces, and regions where sparse events may cause missing texture. Step 2: Generate the Execution Prompt Write a 4-6 sentence instruction for the image model. Use highly descriptive and restrictive keywords. Your generated prompt MUST include: - Explicit instruction to reconstruct the intensity image corresponding to the same input accumulation scale. - Specific guidance on preserving sharp boundaries and recovering plausible texture from sparse event evidence. - Strict negative constraints forbidding ghosting, over-smoothed surfaces, and hallucinated scene content. Goal: Your generated prompt should act as a robust reconstruction blueprint that turns a single event accumulation image into a faithful intensity reconstruction.

### Gemini Prompt.

**\*\*Execution Prompt:\*\*** Reconstruct a grayscale intensity image corresponding to this medium accumulation window event input. Extract and sharpen the faint rectangular geometric object with parallel lines in the lower left and the curved structures above it. Recover plausible surface textures from this highly noisy, sparse data while preserving distinct, sharp object boundaries. Strictly prohibit motion ghosting, over-smoothed surfaces, and the hallucination of scene content unsupported by the raw event traces.

### OpenAI Prompt.


Reconstruct the intensity image that corresponds exactly to the same medium temporal accumulation scale (32) as the provided event frame. Use the signed event evidence: lighten regions with ON-dominant counts, darken regions with OFF-dominant counts, and keep areas with little or no events near neutral mid-gray. Preserve sharp boundaries and continuous contours, particularly along the prominent oval/circular edge in the upper center and the rectangular slab/stripe in the lower center, removing speckle while avoiding blur of these edges. Recover plausible surface texture only where event density supports it using edge-aware, anisotropic smoothing; in sparsely populated zones, fill with low-contrast gradients without inventing fine patterns. Strictly avoid ghosting, double edges, halos, over-smoothed plastic surfaces, or any hallucinated objects or scene content not supported by the events.

**Qwen Prompt.**

Reconstruct the intensity image corresponding to the medium accumulation scale (32), treating the input grain as a distribution of local brightness changes where darker pixels indicate dominant OFF events. Focus on recovering the sharp, high-contrast edges of the geometric structures visible at the bottom and the curved element in the top right, ensuring these features remain distinct and not blurred by the surrounding noise. Convert the stochastic event density into plausible, continuous surface textures for the identified objects while preserving the neutral gray background where no significant change occurred. Strictly forbid the introduction of ghosting artifacts or temporal smearing, as this is a single accumulation snapshot. Do not hallucinate details in low-signal areas; maintain the structural integrity of the scene based solely on the provided event density.

## HDR Imaging

**M1.** tests burst HDR fusion for preserving both highlight and shadow detail.




### Shared Prompt.

Task: Merge this mobile HDR+ burst into a single high dynamic range (HDR) image. Combine complementary information across burst frames to produce a natural tone-mapped result with full detail in both shadows and highlights. Input: A sequence of `{NUM_INPUT_IMAGES}` burst frames from one HDR+ capture (`{INPUT_FRAME_IDS}`; files: `{INPUT_FILENAMES}`). HDR+ capture assumptions: HDR+ bursts typically contain 2-10 raw frames from the same scene, generally captured with the same exposure time and gain on mobile rolling-shutter sensors; inter-frame gaps are usually  $\leq 33$  ms unless a frame is dropped. Constraints: - Burst Fusion: Perform robust multi-frame alignment and merge on same-exposure burst frames; reduce noise by aggregating consistent signal across frames while preserving scene structure. - Dynamic Range Recovery: Recover highlight and shadow detail from inter-frame signal variation after alignment and merge. Do not assume explicit exposure bracketing is present in every burst. - Natural Tone Mapping: Ensure the final tone-mapped image maintains natural local contrast and physically plausible lighting. Strictly avoid unnatural "halos" around high-contrast edges, glowing shadows, or hyper-saturated "grunge" effects typical of exaggerated HDR processing. - De-Ghosting: If there is slight subject/camera motion across burst frames, align static content and suppress ghosting on moving regions, using a stable reference-frame strategy. - Zero Hallucination: Do not invent structural details in saturated highlights or deep shadows if not supported by any burst frame. Output: A photorealistic, perfectly exposed single image featuring maximum dynamic range, natural contrast, and zero blending or alignment artifacts.

**M2.** tests burst HDR fusion for preserving both highlight and shadow detail.

hdr | sampled 5/92 | seed=0



### Planner Prompt.

You are an expert computational imaging assistant. Your task is to analyze one HDR+ burst and write a highly specific "execution prompt" for a downstream HDR fusion model. Input: '{NUM\_INPUT\_IMAGES}' burst frames from one capture ('{INPUT\_FRAME\_IDS}'; files: '{INPUT\_FILENAMES}'). HDR+ capture assumptions: HDR+ bursts typically contain 2-10 raw frames from the same scene, generally captured with the same exposure time and gain on mobile rolling-shutter sensors; inter-frame gaps are usually  $\leq 33$  ms unless a frame is dropped. Step 1: Analyze the Burst Examine the burst to identify recoverable highlights/shadows after alignment+merge, motion regions that may ghost, and low-SNR areas that require robust multi-frame denoising. Step 2: Generate the Execution Prompt Write a 4-6 sentence instruction for the image editing model. Use highly descriptive and restrictive keywords. Your generated prompt MUST include: - Explicit instruction to align and merge the same-exposure burst into one HDR+ style output. - Specific identification of critical regions: highlight structures, deep-shadow textures, and moving objects requiring de-ghosting. - Strict negative constraints forbidding unnatural HDR halos, glowing shadows, or ghosting artifacts. Goal: Your generated prompt should act as a robust algorithmic blueprint for HDR+ style burst fusion (alignment, merge, denoise, tone-map) into a naturally lit, high-dynamic-range scene.

### Gemini Prompt.

Execute a robust alignment and merge of this 4-frame same-exposure burst to synthesize a clean, naturally lit HDR+ style image from a severely underexposed capture. Focus aggressive multi-frame denoising and tone mapping on the deep shadows enveloping the complex machinery to reveal intricate mechanical details, surface textures, and the text on the adjacent informational plaque. Carefully manage the dynamic range to preserve the brighter reflections on the acrylic casing, polished metal components, and the brightly lit background display case without clipping. Ensure precise sub-pixel alignment to maximize the signal-to-noise ratio in this low-light static scene, effectively mitigating any slight camera shake. Strictly avoid unnatural HDR halos around the machine's complex geometry, prevent muddy or artificially glowing shadows during the lifting process, and ensure zero ghosting or alignment artifacts on the sharp mechanical edges.

### OpenAI Prompt.


Align and merge the four same-exposure burst frames (N000, N002, N004, N006) using sub-pixel optical-flow with rolling-shutter aware warping, then fuse with robust outlier rejection for HDR+ style output. Protect highlight detail in the illuminated display case at the top-left, the bright wall/shelf at the top-right, and the specular reflections on the acrylic covers and metal rods/knobs of the machine; avoid clipping while maintaining clean edge contrast. Lift and denoise deep-shadow textures in the machine's base, pipes and arm recesses, the pedestal, the radiator area behind, and the text panel on the left, preserving fine machining marks and printed text without waxy smoothing. Apply strong de-ghosting for any micro-parallax or flicker in thin rods, plexiglass edges, and reflective surfaces, rejecting inconsistent pixels and preventing double edges. Tone-map to a natural museum lighting look with neutral colors and moderate local contrast. Strictly forbid HDR halos, glowing or lifted shadows around bright boundaries, over-sharpening, color shifts, and any ghosting artifacts.

### Qwen Prompt.

Align and merge the four burst frames into a single HDR image, focusing on lifting the heavy shadows of the large green mechanical device to reveal intricate gear and lever details while retaining the integrity of the bright overhead lights in the background display case. Pay specific attention to the clear acrylic protection boxes, ensuring their specular highlights are crisp and free of blooming or halo artifacts. Apply aggressive temporal denoising to the dark, underexposed regions of the machine body and floor to reduce noise while preserving sharpness. Strictly enforce natural tone mapping to avoid the 'glowing' shadow look typical of aggressive HDR, and ensure no ghosting artifacts appear from minor inter-frame camera jitter around the static object edges.

### M3. tests generation of a plausible single HDR+ burst frame from a reference HDR image.

hdr | best\_psnr\_frame | sampled 5/153 | seed=0



### Planner Prompt.

You are an expert in computational imaging, working on the image formation model for compressive sensing. Input: one HDR/tone-mapped reference image. Task: generate one plausible HDR+ burst frame (single output image), not the full burst.

First infer and write the forward model equation, then write an execution prompt for a downstream image editor. Required response format: 1. 'FORWARD\_MODEL:' - Write an exposure and sensor model for one burst frame, for example mapping irradiance to a captured frame under a certain exposure setting (ISO, shutter speed, aperture, gain) with rolling-shutter sampling and sensor noise. - State that HDR+ burst frames are typically same-exposure/same-gain with short inter-frame gaps and slight handheld perturbations. - Describe how one frame should differ from the latent radiance reference (noise, tiny pose shift, rolling-shutter effects) while remaining physically plausible. 2. 'EXECUTION\_PROMPT:' - Write a strict 4-6 sentence prompt that instructs the image editor to generate exactly one burst frame from the provided reference. - Require realistic mobile sensor behavior: subtle jitter/misalignment cues, plausible noise, and no dramatic geometry change. - Forbid multi-frame output, exaggerated HDR halos, stylization, text overlays, and unrelated content additions. Hard constraints: - Equation-first ordering is mandatory: 'FORWARD\_MODEL' must appear before 'EXECUTION\_PROMPT'. - Output must be one representative burst frame only. - Keep padded black regions black if present.

### Gemini Prompt.

\*\*FORWARD\_MODEL:\*\* The formation of a single burst frame in an HDR+ pipeline (e.g., constant-exposure burst photography) can be modeled by mapping the dynamic scene irradiance to a discrete, noisy digital signal. For a pixel location  $\$x\$$  and frame index  $\$k\$$ , the captured raw signal  $\$Y_k(x)\$$  is given by:  $\$Y_k(x) = \text{Quantize}(\left( g \cdot \int_{t_k}^{t_k + t_{rs}}(x) \cdot E(W_k(x, t), t) dt + \mathcal{P}(\lambda) + \mathcal{N}(0, \sigma^2) \right)\$$  Where: \*  $\$E(W_k(x, t), t)\$$  is the latent scene irradiance at time  $\$t\$$ , warped by  $\$W_k\$$  which models slight handheld camera shake and scene motion relative to the reference frame. \*  $\$t_k\$$  is the base timestamp of the  $\$k\$-th$  frame. \*  $\$t_{rs}(x)\$$  models the rolling-shutter temporal offset for the row containing pixel  $\$x\$$ . \*  $\$\Delta t\$$  is the short exposure time (shutter speed), kept constant across the burst to prevent highlight clipping and simplify alignment. \*  $\$g\$$  is the constant analog/digital gain (ISO). \*  $\mathcal{P}(\lambda)$  represents signal-dependent Poisson shot noise. \*  $\mathcal{N}(0, \sigma^2)$  represents signal-independent Gaussian read noise. \*  $\text{Quantize}(\cdot)$  represents the ADC conversion to digital numbers. In HDR+ systems, all frames in the burst share the exact same short exposure ( $\Delta t$ ) and gain ( $g$ ). Therefore, a single frame from this burst differs from the final tone-mapped reference by being significantly noisier (especially in shadow regions due to the short exposure), exhibiting a flat/linear or unpolished tonal curve before merging, and containing microscopic misalignments (a few pixels of translation/rotation) or slight rolling-shutter skew caused by hand tremor during the short inter-frame gaps. \*\*EXECUTION\_PROMPT:\*\* Act as a computational photography simulator and generate exactly one realistic, unmerged burst frame derived from the provided HDR reference image. Degrade the polished HDR appearance by applying characteristic mobile sensor noise, specifically introducing visible luma and chroma noise that heavily impacts the shadow regions to simulate a short, constant-exposure capture. Introduce a very subtle, almost imperceptible global shift or mild rolling-shutter skew to mimic natural handheld camera jitter, without causing dramatic geometric changes. Flatten the localized tone mapping to make the lighting look like a single, slightly underexposed raw-like capture rather than a merged HDR result. Strictly forbid the generation of multi-frame collages, exaggerated HDR halos, artistic stylization, text overlays, or new structural content, and ensure any padded black borders remain pure black.

### OpenAI Prompt.


FORWARD\_MODEL: - One HDR+ burst frame  $k$  is modeled from the latent scene irradiance  $E(x)$  via a rolling-shutter sensor with constant exposure: ISO  $G_{iso}$ , shutter  $T_e$ , aperture  $f$  (effective area  $A \propto 1/f^2$ ), analog gain  $g_a$  and digital gain  $g_d$ . The row  $y$  starts integrating at  $t_{row}(y) = t_0 + y \cdot t_{rs}$ , and each pixel  $u = (x, y)$  integrates for  $T_e$ . - Expected photons:  $\_k(u) = A \cdot s(u) \cdot \int_{t_{row}(y)}^{t_{row}(y)+T_e} E(u; (t)) dt$ , where  $s(u)$  is lens shading,  $is$  QE, and  $(u; (t))$  maps the pixel to the scene under a slight hand-held pose that drifts during readout (tiny translation/rotation). - Measurement (RAW):  $z_k(u) = Q \{ g_d [ \text{Poisson}(\_k(u)) ] + N(0, \sigma^2(G_{iso})) \} + b_{black}$ , with  $Q$  quantization, Poisson shot noise, Gaussian read noise, and black level  $b_{black}$ . Rolling-shutter induces subtle vertical skew; demosaic/WB later produces the rendered frame. - HDR+ bursts typically use same exposure/same gain across frames with short inter-frame gaps (10-20 ms) and small handheld perturbations. Compared to the tone-mapped reference radiance, a single frame should exhibit slightly higher noise (more visible in shadows), tiny sub-pixel misalignment and minor RS skew, while preserving scene geometry and content. - Plausible parameters for this daylight scene:  $f/2.0$ , ISO 160,  $T_e$  1/120 s, per-frame pose jitter 1 px translation and  $0.3^\circ$  rotation, row readout  $t_{rs}$  such that full-frame readout 1/30 s. EXECUTION\_PROMPT: Generate exactly one realistic HDR+ burst frame from the provided reference, assuming ISO 160, 1/120 s shutter,  $f/2.0$ , same exposure/gain as other (unseen) frames. Apply a sub-pixel handheld shift (1 px) with  $0.3^\circ$  rotation and mild rolling-shutter vertical skew consistent with a 1/30 s full-frame readout; keep global geometry nearly unchanged. Add physically plausible Poisson-Gaussian sensor noise with more visible grain in shadowed regions and very light highlight quantization, without introducing HDR halos. Do not stylize, sharpen aggressively, add text/graphics, or change colors unnaturally; keep any padded black regions pure black. Output a single frame only, aligned closely to the reference but with the subtle jitter and noise cues of a handheld mobile capture.

### Qwen Prompt.

FORWARD\_MODEL: The forward model for a single HDR+ burst frame  $\$I_{burst}\$$  can be described as a mapping from the latent scene radiance  $\$L\$$  through the camera sensor physics, incorporating exposure parameters and noise. The equation is given by:  $\$I_{burst} = \mathcal{Q} \left( \mathcal{R} \left( L \cdot \frac{g}{\Delta t} \cdot \tau \right) + \eta_{shot} + \eta_{read} \right) \circ \mathcal{T}_{jitter}\$$  where  $\mathcal{R}\$$  is the sensor's non-linear response function,  $\$g\$$  is the ISO gain,  $\$\Delta t\$$  is the exposure time,  $\$\tau\$$  is the normalization constant,  $\mathcal{Q}\$$  is the quantization to digital values,  $\eta_{shot}$  represents Poisson-Gaussian noise (shot and read noise), and  $\mathcal{T}_{jitter}\$$  models the slight affine transformation due to handheld micro-movements. HDR+ burst frames are typically captured with short exposure times ( $\Delta t$ ) and moderate gain to prevent saturation in high-dynamic-range scenes, resulting in a frame that is noisier and potentially slightly underexposed compared to the final merged HDR output. The generated frame should differ from the latent radiance reference by introducing realistic photon shot noise, sensor read noise, and a sub-pixel geometric shift to simulate the physical reality of a handheld burst capture, while strictly avoiding the global tone-mapping and sharpening present in the reference. EXECUTION\_PROMPT: Generate a single, realistic mobile sensor burst frame derived from the provided reference image. The image should appear slightly underexposed compared to the final HDR result to simulate a short-exposure capture intended for multi-frame merging, with visible high-frequency sensor noise and slight chromatic aberration. Apply a subtle, random affine transformation (jitter) to simulate handheld micro-movements between frames, ensuring the subject's pose remains consistent but slightly misaligned relative to the background geometry. Preserve the original color balance and lighting conditions without applying aggressive tone-mapping, sharpening, or HDR halos. Do not output multiple frames, add text overlays, or alter the scene content, ensuring the output looks like a raw input for an HDR pipeline.

## Inpainting

**M1.** tests masked image completion while preserving scene structure and texture continuity.




### Shared Prompt.

Task: Perform high-fidelity inpainting to seamlessly fill the missing (blacked-out/masked) regions of the input image.  
 Input: An image with masked (missing) regions and its corresponding binary mask image. Constraints: - Mask Semantics: Treat pixels that are exactly pure black (#000000) in the masked image as missing regions to be inpainted. Use the provided binary mask as the authoritative region map, since non-missing content elsewhere may also contain dark/black pixels. - Strict Mask Adherence: You must not alter a single pixel outside of the explicitly masked regions. The original, unmasked image content must remain 100% identical in structure, color, and sharpness. - Seamless Boundary Blending: Ensure perfect continuity at the edges of the mask. There must be no visible seams, lighting shifts, or texture mismatches where the generated content meets the original pixels. - Semantic & Perspective Consistency: The generated content within the masked region must logically align with the surrounding visual context. Match the existing depth of field, perspective lines, and lighting direction perfectly. - Texture Matching: The newly generated pixels must mimic the exact noise floor, grain, and surface textures of the surrounding original image to avoid looking artificially smooth or digitally inserted.  
 Output: A complete, unmasked version of the image where the missing gaps have been logically filled without any alteration to the original surrounding content.

**M2.** tests masked image completion while preserving scene structure and texture continuity.

inpainting | sampled 5/73 | seed=0



### Planner Prompt.

You are an expert computational imaging assistant. Your task is to analyze an image with missing (blacked-out) regions and write a highly specific "execution prompt" for a downstream image inpainting model. Input: An image with masked (missing) regions and its corresponding binary mask image. Step 1: Analyze the Context Use the provided binary mask as the authoritative missing-region definition. In the masked image, pixels that are exactly pure black (#000000) indicate missing regions, but note that some valid scene content may also be dark; rely on the mask to disambiguate. Then examine the visual information immediately surrounding the masked region and deduce what logical object, texture, or background is missing (e.g., "The mask covers the lower half of a brick wall and a wooden bench," or "The missing area should contain the continuation of a cloudy sky and the tip of a mountain"). Identify the lighting direction and depth of field. Step 2: Generate the Execution Prompt Write a 4-6 sentence instruction for the image editing model. Use highly descriptive and restrictive keywords. Your generated prompt MUST include: - An explicit description of exactly what objects, textures, or colors need to be generated inside the mask to complete the scene logically. - Specific instructions on lighting, perspective, or focus needed to match the surrounding unmasked areas. - Strict negative constraints forbidding the model from altering any pixels outside the designated mask or introducing logically inconsistent objects. Goal: Your generated prompt should act as a perfect contextual blueprint, allowing the editing model to seamlessly reconstruct the missing data without touching the original image.

### Gemini Prompt.

The mask primarily obscures portions of the woman's face, upper body, and the wall behind her, as well as a large section on the left side near the wall. Inpaint the missing sections of the woman's face and upper body, continuing her features, the brown hat, and the grey cardigan. Reconstruct the missing parts of the textured, beige wall behind her, matching the rough surface and lighting. Ensure the inpainted areas align seamlessly with the existing visible parts of the woman and the wall. The lighting should remain consistent, coming from the upper right, casting soft shadows on her face and the wall. Do not alter any areas outside the mask or introduce new objects not implied by the existing context.

### OpenAI Prompt.


Execution prompt for inpainting: - Fill the masked regions with the continuation of the scene: a seated vendor against a two-tone stucco wall, a tan felt hat, the person's natural face and dark braided hair, a gray wool sweater, clasped hands resting on a blue skirt with small white dot pattern, and a pile of pink/red onions with tangled roots and green stalks on a dark blue cloth with bits of straw on a cobblestone ground. - Preserve the wall's rough texture and the horizontal color break midway up the wall, and extend the ground's stones and scattered straw consistently under the produce. - Lighting should be soft, overcast daylight with gentle, diffuse highlights; shadows fall subtly to the right, matching the existing scene. - Keep the perspective at eye level and maintain moderate depth of field: the person and onions in sharp focus, background wall slightly softer but not blurred. - Do not alter any pixels outside the mask, do not introduce new objects, people, text, or different clothing styles, and avoid color shifts or changes to the wall seam, blanket edges, or existing contours.

### **Qwen Prompt.**

Reconstruct the scene content obscured by the black shapes defined in the binary mask, specifically filling in the missing portions of the rough beige stucco wall in the upper left and center. Generate the continuation of the person's brown felt hat and grey knitted cardigan in the upper right and center areas, ensuring the fabric texture and folds align with the visible clothing. In the lower central region, restore the pile of red onions with green stalks and the surrounding straw on the ground, matching the organic shapes and colors. On the right side, complete the grey cardigan sleeve and the blue patterned skirt fabric, maintaining the soft focus and natural lighting of the outdoor setting. Strictly forbid any alterations to the pixels outside the mask boundaries, preserving the unmasked hands, the lower skirt, and the ground details exactly as they appear.


*Random Mask Subsampling (Ratios 0.010, 0.020, 0.040, 0.060, 0.080)*

**M1.** tests reconstruction from randomly masked subsampled measurements at a 0.010 sampling ratio.




**Additional Ratios (M1).**


rand\_mask\_subsample | ratio\_020 | sampled 5/88 | seed=0




rand\_mask\_subsample | ratio\_040 | sampled 5/89 | seed=0



rand\_mask\_subsample | ratio\_060 | sampled 5/87 | seed=0



rand\_mask\_subsample | ratio\_080 | sampled 5/87 | seed=0



### Shared Prompt.


Task: Reconstruct the full-resolution RGB image from randomly masked imaging measurements containing only partial, undersampled information. Input: A randomly masked measurement image and its corresponding binary mask image. Constraints:

- Mask Semantics: Treat masked-out regions in the measurement as missing data represented by pure black (#000000), and use the provided binary mask as the authoritative missing-region map.
- Sparsity & Structural Prior: Assume the underlying image is sparse in a natural image basis. Enforce global structural consistency first. Recover sharp, high-contrast edges while strictly keeping smooth regions (like skies or blank walls) clean and uniform.
- Artifact Suppression: Actively suppress incoherent noise and sampling artifacts characteristic of sub-Nyquist sampling. Do not introduce ringing, overshoot, or artificial frequencies.
- Conservative Complexity: Prefer physically plausible, minimal-complexity solutions. Preserve the correct geometry, structural proportions, and perspective without artistic enhancement.
- Zero Hallucination: Do not hallucinate fine textures, invent new objects, or add high-frequency details that are not mathematically supported by the underlying sparse structural data.

Output: A photorealistic, clean, artifact-free reconstructed image featuring natural contrast and lighting, perfectly faithful to the undersampled measurements.

M2. tests reconstruction from randomly masked subsampled measurements at a 0.010 sampling ratio.

rand\_mask\_subsample | ratio\_010 | sampled 5/90 | seed=0




## Planner Prompt.


You are an expert computational imaging assistant. Your task is to analyze an image formed by random sub-sampling (characterized by partial information and incoherent sampling artifacts) and write a highly specific "execution prompt" for a downstream reconstruction model. Input: A randomly masked measurement image and its corresponding binary mask image. Step 1: Analyze the Measurements Use the provided binary mask as the authoritative map of missing samples. In the measurement image, masked-out regions are represented by pure black (#000000), but valid scene content can also contain dark pixels; rely on the mask for disambiguation. Then examine the undersampled image to deduce the global structural composition. Identify the primary sharp boundaries that need recovery, and distinguish them from the naturally smooth regions (e.g., gradients, skies, or flat surfaces) that are currently corrupted by incoherent sampling noise. Step 2: Generate the Execution Prompt Write a 4-6 sentence instruction for the image editing/reconstruction model. Use highly descriptive and restrictive keywords. Your generated prompt MUST include: - Explicit identification of the image formation process as partial, randomly under-sampled measurements. - Specific identification of the deduced geometric structures that need sharp recovery, contrasted with specific smooth regions that need aggressive artifact suppression (e.g., "Recover the sharp geometric outlines of the bridge cables while completely smoothing the incoherent sampling noise in the sky"). - Strict negative constraints forbidding the model from hallucinating fine details, inventing unsupported textures, or altering the natural lighting. Goal: Your generated prompt should act as a perfect algorithmic blueprint, guiding the reconstruction model to enforce a natural image sparsity prior, balancing sharp edge recovery with smooth region denoising.

## Additional Ratios (M2).


rand\_mask\_subsample | ratio\_020 | sampled 5/84 | seed=0




rand\_mask\_subsample | ratio\_040 | sampled 5/81 | seed=0



rand\_mask\_subsample | ratio\_060 | sampled 5/84 | seed=0



rand\_mask\_subsample | ratio\_080 | sampled 5/84 | seed=0



### Gemini Prompt.

Reconstruct the original image from these partial, randomly under-sampled measurements using the provided binary mask to identify valid samples. Accurately recover the sharp geometric boundaries of the prominent arched stone bridge, the structural outlines of the background buildings, and the distinct silhouette of the skyline. Concurrently, apply aggressive artifact suppression to completely smooth the incoherent sampling noise corrupting the dark, uniform sky and smooth foreground regions. Strictly avoid hallucinating fine details, inventing unsupported textures in the foliage or stonework, or altering the natural low-light scene illumination. Enforce a strong natural image sparsity prior to perfectly balance sharp edge fidelity with smooth region denoising.

### OpenAI Prompt.

Use the binary mask to treat only the masked pixels as missing data and reconstruct the scene from partial, randomly under-sampled measurements. Recover the sharp geometric outlines of the stone arch bridge: the outer arc of the large central arch, the intrados and keystone region, the straight bridge deck and parapet with regularly spaced openings, plus the crisp rooflines and facades of the clustered hillside buildings and the riverbank edges. Maintain clean, edge-preserving separation between the bridge, buildings, and vegetation, keeping tree masses as coarse shapes without inventing leaf-level texture. Aggressively suppress incoherent sampling noise in the smooth sky and on the water surface and reflections, rendering them as low-frequency gradients with only gentle ripples where measurements support them. Preserve the original lighting and color balance; do not hallucinate fine brickwork, signage, text, windows, people, or any new structures not supported by the measured samples. Enforce a natural-image sparsity prior: strong edge recovery on architectural boundaries, heavy denoising on flat regions, and no alteration of scene geometry.


### Qwen Prompt.

The input image consists of partial, randomly under-sampled measurements of a low-light scene, characterized by incoherent sampling artifacts and missing data regions defined by the binary mask. Analyze the faint diagonal structures in the upper right to deduce and recover the sharp geometric outlines of suspension bridge cables and support towers. Simultaneously, aggressively smooth the large, naturally dark regions representing the sky and water to suppress the high-frequency noise

without blurring the structural edges. Strictly forbid the model from hallucinating fine details, inventing unsupported textures, or altering the natural lighting and color balance of the night scene.

## Super-Resolution (x4)

M1. tests 4x image super-resolution from a lower-resolution observation.




### Shared Prompt.

Task: Perform 4x super-resolution on this 256x256 low-resolution image to produce a sharp, highly detailed 1024x1024 high-resolution output. Input: A downsampled low-resolution image. Constraints: - Spatial Scaling: Strictly upscale the image dimensions by exactly 4x (from 256x256 to 1024x1024 pixels). - Fidelity & Detail: Enhance the resolution by producing a high-resolution version with sharp edges, fine textures, and realistic detail that is mathematically consistent with the original low-resolution content. - Anti-Hallucination: Do not invent semantic details. Do not hallucinate legible text from blurred pixels, invent specific facial features, or add objects not implied by the low-resolution geometry. Only interpolate physically plausible high-frequency data. - Artifact Suppression: Avoid the "watercolor," "oil painting," or "plastic" smoothing artifacts common in generative upsampling. Retain natural image grain and physically plausible micro-contrast. Output: A photorealistic 1024x1024 image that looks exactly like a native high-resolution capture of the original scene.

M2. tests 4x image super-resolution from a lower-resolution observation.

super\_resolution | x4 | sampled 5/88 | seed=0



### Planner Prompt.

You are an expert computational imaging assistant. Your task is to analyze a 256x256 low-resolution image and write a highly specific "execution prompt" for a downstream 4x super-resolution model. Input: A downsampled low-resolution image. Step 1: Analyze the Degradation Examine the low-resolution image to deduce the underlying semantic content. Identify specific materials, textures, and high-contrast boundaries that have been lost to the spatial sub-sampling (e.g., "The blurry region in the center is coarse animal fur; the jagged diagonal line is the edge of a brick wall"). Step 2: Generate the Execution Prompt Write a 4-6 sentence instruction for the image upscaling model. Use highly descriptive and restrictive keywords. Your generated prompt MUST include: - Explicit instruction to perform a 4x super-resolution upscale from 256x256 to 1024x1024. - Specific identification of the underlying textures that need physically plausible recovery (e.g., "Recover the fine, distinct strands of the animal fur and the sharp geometric edge of the brick wall"). - Strict negative constraints forbidding the model from hallucinating recognizable but incorrect details (like fake text) or applying unnatural "watercolor" smoothing filters. Goal: Your generated prompt should act as a perfect semantic guide, helping the upscaling model intelligently interpolate the missing high-frequency data for those specific textures without inventing alien features.

### Gemini Prompt.

\*\*Degradation Analysis:\*\* The spatial sub-sampling has blurred the individual blades of grass into soft green patches. High-frequency details on the distant suspension bridge (cables and towers) are aliased and faint. The woman's tan leather jacket lacks surface grain, and the vents on her bicycle helmet are pixelated. Background figures and the distant foggy hills have lost sharp boundary definitions. \*\*Execution Prompt:\*\* Perform a 4x super-resolution upscale from 256x256 to 1024x1024. Recover the individual grass blades in the field, eliminating the current blurred patches. Reconstruct the fine vertical cables of the distant bridge and the crisp geometric vents on the bicycle helmet. Restore the realistic surface grain of the leather jacket and the sharp boundaries of the distant figures. Do not hallucinate fake text, alien structural details, or phantom faces. Strictly avoid applying any unnatural watercolor smoothing filters.

### OpenAI Prompt.


Perform a 4x super-resolution upscale from 256x256 to 1024x1024, preserving the original scene: a person in the foreground on a broad grass field with distant hills, light fog, a suspension bridge, and a clear blue sky. Recover physically plausible fine textures: distinct short blades of grass with subtle shadowing, the grain and stitching seams of the tan leather jacket, the denim weave on the jeans, crisp vents and metallic/plastic ridges on the bike helmet, and the faint fabric pattern on the shirt. Reconstruct sharp geometric boundaries: the straight horizon between grass and distant hills/sky, clean vertical towers and thin diagonal cables of the bridge, and well-defined edges on the person's clothing and helmet, while keeping the hills and bridge partially softened by fog. Maintain natural lighting and gradients; avoid oversharpening halos, banding, or noise, and do not invent detailed facial features. Strictly avoid hallucinating text, logos, vehicles, extra people, or new architectural elements, and do not apply watercolor-like smoothing or introduce artificial high-frequency patterns inconsistent with grass, fabric, leather, metal, or suspension cables.

### **Qwen Prompt.**

Perform a 4x super-resolution upscale from 256x256 to 1024x1024, focusing on recovering high-frequency details lost in the initial blur. Specifically, reconstruct the fine, distinct blades of grass in the foreground to replace the uniform green wash, ensuring natural variation in height and color. Resolve the texture of the tan jacket, recovering realistic fabric folds and stitching lines, and clearly define the ventilation slots on the bicycle helmet. In the distance, sharpen the faint reddish structure of the Golden Gate Bridge and the hazy mountain range to reveal their geometric forms. Strictly forbid the application of unnatural "watercolor" smoothing filters or the hallucination of fake text, ensuring all recovered features remain physically plausible and consistent with the original scene.

## Time-of-Flight

**M1.** tests scene reconstruction from time-of-flight imaging measurements.




### Shared Prompt.

Task: Reconstruct a per-pixel depth map from four raw time-of-flight (ToF) correlation measurements of the same scene. Input: Four phase-shifted raw ToF correlation images captured at 0 deg, 90 deg, 180 deg, and 270 deg with {TOF\_MODULATION\_FREQUENCY} modulation frequency. Constraints: - Multi-frame consistency: Use all four correlation frames jointly. Do not treat any single frame as a standalone depth estimate. - Geometric fidelity: Preserve object boundaries, thin structures, and depth discontinuities without staircase artifacts or edge fattening. - Noise robustness: Suppress phase noise and invalid speckle-like artifacts while keeping physically plausible depth gradients. - MPI suppression: Remove multi-path interference at corners while preserving true geometric discontinuities. - Metric integrity: Output a depth image whose values are spatially and numerically consistent with the measured phase information. Do not hallucinate structures that are not supported by the four inputs. - Pad-Region Handling: If black padded borders are present, treat only the non-black valid region as scene content. Output: A clean, physically consistent depth map for the scene.

**M2.** tests scene reconstruction from time-of-flight imaging measurements.

tof | sampled 5/97 | seed=0



### Planner Prompt.

You are an expert computational imaging assistant. Your task is to analyze four phase-shifted raw ToF correlation images of the same scene and write a highly specific "execution prompt" for a downstream depth-reconstruction model. Input: Four phase-shifted raw ToF correlation images captured at 0 deg, 90 deg, 180 deg, and 270 deg with {TOF\_MODULATION\_FREQUENCY} modulation frequency. Step 1: Analyze the Measurements Inspect the four correlation frames jointly to identify reliable depth boundaries, low-signal regions, and areas prone to phase noise or ambiguity (for example glossy surfaces, dark regions, or distant background). Step 2: Generate the Execution Prompt Write a 4-6 sentence instruction for the image model. Use highly descriptive and restrictive keywords. Your generated prompt MUST include: - Explicit instruction to reconstruct one metric-consistent depth map from all four phase-shifted ToF inputs. - Specific guidance to preserve sharp depth discontinuities at object edges while denoising unstable regions. - Explicit suppression of multi-path interference at corners while keeping physically valid corner geometry. - Strict negative constraints forbidding geometric hallucinations, edge blurring, or inconsistent depth layering. - Specific guidance to ignore black padded border regions during inference but preserve those regions as black in the output image. - Explicit handling of black padded borders: ignore padded black areas when inferring scene content, and preserve those padded areas as black in the output. Goal: Your generated prompt should act as a precise inversion blueprint that converts the four ToF correlation measurements into a physically plausible depth map.

### Gemini Prompt.

Analyze the four raw ToF correlation images to produce a highly detailed execution prompt for a depth-reconstruction model. The input correlation frames show a scene captured with a modulation frequency of 20 MHz. The scene features a flat rectangular block serving as a base. Resting on top of this block is a complex object composed of smaller blocks and a wheel-like shape, possibly a toy construction. The correlation images present varying intensity patterns due to the phase shifts (0, 90, 180, 270 degrees). Key observations: 1. **Object Boundaries:** Sharp depth discontinuities exist at the edges of the base block and the object on top. These boundaries are clear in the correlation images, particularly where foreground objects contrast with the background. 2. **Surfaces and Textures:** The surfaces of the base block and the objects on top appear relatively diffuse, but some areas might be darker or have lower reflectivity, leading to weaker

correlation signals and potential noise in those regions. 3. **Potential Multi-path Interference (MPI):** The corners where the objects on top meet the base block, and the internal corners of the objects themselves, are susceptible to multi-path interference due to light bouncing between surfaces. 4. **Low-Signal Areas:** The background behind the objects is darker, indicating lower signal return and potential phase noise in these distant or less reflective regions. 5. **Padded Borders:** There is a substantial black padded border surrounding the active image area in all four frames. Execution Prompt formulation: \* **Core Task:** Reconstruct a single, metric-consistent depth map using all four phase-shifted ToF inputs (0, 90, 180, 270 degrees) captured at 20 MHz. \* **Edge Preservation and Denoising:** Emphasize preserving the sharp depth discontinuities at the edges of the base block and the objects resting on it. Simultaneously, denoise areas with unstable signals, such as the darker background regions. \* **MPI Suppression:** Explicitly instruct the model to suppress multi-path interference, particularly at the corners and junctions of the objects and the base block, while maintaining the physical geometry of these corners. \* **Negative Constraints:** Strictly forbid geometric hallucinations, blurring of the sharp edges separating the objects from the background, and inconsistent depth layering, ensuring a physically plausible reconstruction. \* **Handling Padded Borders:** Specifically guide the model to ignore the black padded border regions during inference, ensuring they do not influence the depth estimation of the scene, and mandate that these padded areas are preserved as black in the final output image. This analysis leads directly to the specific execution prompt. Execution Prompt: Synthesize a single metric-consistent depth map from the four provided ToF correlation images captured with phase shifts of 0, 90, 180, and 270 degrees at a 20 MHz modulation frequency. Carefully preserve the sharp depth discontinuities at the boundaries of the base block and the objects on top, while applying robust denoising to stabilize the depth estimates in the darker, low-signal background areas. Explicitly suppress multi-path interference artifacts at the corners and junctions where the objects meet the base block, ensuring the physical validity of the corner geometry is maintained. Strictly prohibit the introduction of geometric hallucinations, blurring of object edges, or inconsistent depth layering in the reconstructed map. Finally, ignore the prominent black padded border regions surrounding the scene during inference, and ensure these padded areas are strictly preserved as black in the output depth map.

### OpenAI Prompt.

Step 1: Measurement analysis - The four correlation frames show a small block-like object on a pedestal in the bottom-center, surrounded by large black padded borders; signal is strong on the object and base, weaker on the rear wall, and very low elsewhere. - Sharp depth boundaries exist at the object edges and pedestal edges; the corner between the two walls and pedestal edges are prone to multi-path and phase instability. - Dark regions and most of the padded borders have near-zero correlation, so they should be treated as invalid/low-SNR to avoid noisy depth. - Preserve crisp geometry on the object and base while denoising the dim background; watch for phase wrapping in low-signal areas. Execution prompt for the depth-reconstruction model - Reconstruct one metric-consistent depth map from all four phase-shifted ToF inputs (0°, 90°, 180°, 270°) captured at {TOF\_MODULATION\_FREQUENCY\_MHZ} MHz by demodulating the complex correlation:  $\phi = \text{atan2}(I_{90I270}, I_{0I180})$ , amplitude  $A = \sqrt{(I_{0I180})^2 + (I_{90I270})^2}$ , and convert phase to range  $R = (\phi/2) \cdot c/(2f)$ . - Use amplitude-gated, edge-preserving processing: keep sharp depth discontinuities at object and pedestal boundaries, apply denoising only within regions of similar phase, and mark very low-A areas (dark background) as invalid rather than smoothing across edges. - Perform robust 2 phase unwrapping with spatial continuity and amplitude support to prevent wrap-induced layering; maintain crisp, planar geometry for the object faces and the pedestal top. - Suppress multi-path interference at corners and occluding edges by favoring the direct-path solution with highest A and local phase consistency, rejecting secondary reflections while keeping physically valid right-angle corner geometry. - Strict negative constraints: no geometric hallucinations, no edge blurring, and no inconsistent front/back depth layering anywhere in the scene. - Explicitly handle the black padded borders: ignore padded black areas when inferring scene content, and preserve those padded areas as black in the output depth image.

### Qwen Prompt.

Reconstruct a single, metric-consistent depth map by fusing the four provided phase-shifted ToF correlation frames. Aggressively denoise the low-signal background regions while maintaining the structural integrity of the central object and pedestal. Preserve sharp depth discontinuities at the object boundaries and pedestal edges, explicitly suppressing multi-path interference at corners while retaining physically valid corner geometry. Strictly forbid geometric hallucinations, edge blurring, or inconsistent depth layering; the output must represent a physically plausible 3D geometry. Ignore the black padded border regions during the inference process to focus on the active scene content, but ensure these black padded areas are preserved as black in the final output image.

## White Balance

**M1.** tests illumination correction to recover a naturally white-balanced image.



### Shared Prompt.

Task: Correct the white balance of this image. Adjust the color temperature and tint so that neutral surfaces appear neutral and the overall color rendition is accurate and natural. Input: An image with a color cast captured under a non-neutral illuminant. Constraints: - Neutral Reference Targeting: Utilize the color picker tool to identify surfaces in the image that should be pure white or 18% gray when available. If neutral references are partially visible or missing due to cropping, infer a physically plausible global correction from scene-wide illumination cues without local recoloring. - Global Shift Only: Apply a mathematically uniform adjustment to the global color temperature (Kelvin) and tint (green/magenta axis) to neutralize the false color cast. - Exposure & Contrast Integrity: Do not alter the image's overall exposure, luminance levels, or local contrast. The brightness of the highlights and shadows must remain identical to the original image. - Zero Hallucination: Do not selectively "paint" or recolor individual objects. The adjustment must act as a global optical filter inversion, preserving the true underlying saturation of non-neutral objects. Output: A perfectly color-balanced image where the lighting appears natural and all neutral tones are rendered completely free of color casts.

**M2.** tests illumination correction to recover a naturally white-balanced image.

white\_balance | sampled 5/95 | seed=0



### Planner Prompt.

You are an expert computational imaging assistant. Your task is to analyze an image formed with an incorrect white balance (characterized by an unnatural global color cast) and write a highly specific "execution prompt" for an image restoration model. Input: An image with a color cast captured under a non-neutral illuminant. Step 1: Analyze the Degradation and Scene Examine the image to identify the nature of the color cast (e.g., is it overly warm/amber from tungsten lighting, overly cool/blue from deep shade, or tinted green from fluorescent lights?). Scan the scene to identify a specific, structurally logical object that should act as a neutral reference point when available (e.g., a white piece of paper, a gray concrete wall, or a white shirt). If such neutral references are partially visible or absent due to cropping, infer the global correction from overall illumination and material statistics. Step 2: Generate the Execution Prompt Write a 4-6 sentence instruction for the image editing model. Use highly descriptive and restrictive keywords. Your generated prompt MUST include: - Explicit identification of the specific global color cast that needs to be neutralized (e.g., "Remove the heavy amber/tungsten color cast"). - Specific identification of the object in the scene that the model should use as its neutral reference for the color picker adjustment when available (e.g., "Use the white coffee cup on the table as the neutral white reference point"), or explicit instruction to use scene-level global cues when no reliable neutral patch exists. - Strict negative constraints forbidding the model from altering the global exposure, painting localized colors, or changing the structural details of the image. Goal: Your generated prompt should act as a perfect algorithmic blueprint, guiding the restoration model to optically invert the specific lighting temperature without relying on blind "auto-color" algorithms.

### Gemini Prompt.

Correct the heavy amber/tungsten color cast pervading this image. The scene is significantly tinted orange due to warm artificial lighting. To neutralize this global tint, use the white column visible in the background on the right as your neutral reference point. Adjust the image's overall color temperature to render this column a true, neutral white, thereby restoring accurate colors to the rest of the scene, including the color checker chart in the foreground. Do not alter the image's overall brightness or contrast. Ensure the structural integrity of the scene remains intact; do not paint localized colors or apply any non-global adjustments. Ensure all colors, particularly on the color checker, accurately

reflect the new, balanced temperature.

**OpenAI Prompt.**



Remove the heavy amber/yellow tungsten color cast affecting the entire frame. Use the X-Rite ColorChecker card in the lower-left as the neutral reference; sample one of its gray patches (preferably the 18% mid-gray) to set the white balance. Apply a global correction by shifting temperature toward cooler/blue and adjust the green/magenta tint only as needed until the sampled gray reads neutral (RGB balanced). Do not alter global exposure, contrast, saturation, or add any local color painting; avoid sharpening, noise reduction, or vignette changes. Preserve all structural details, textures, and the original composition while performing only the white-balance recalibration.

**Qwen Prompt.**



Remove the pervasive heavy amber and orange color cast caused by warm indoor tungsten lighting. Use the grayscale patches located in the bottom row of the X-Rite ColorChecker chart in the bottom-left foreground as the definitive neutral reference point for the white balance adjustment. Specifically, instruct the model to neutralize the color of the medium gray patches in the chart so they appear achromatic (neutral gray) rather than yellowish-orange. Apply this temperature correction globally to all surfaces, ensuring the white pillars and ceiling lights appear white rather than yellow. Strictly prohibit any adjustments to global exposure, brightness, or contrast, and ensure no structural details or background blur are altered during the restoration process.

## Lens Design



- HFOV: 0.75 rad
- FNUM: 1.8
- DIAG: 8.0 mm
- Elements: 6





- HFOV: 0.70 rad
- FNUM: 2.0
- DIAG: 7.66 mm
- Elements: 6





- HFOV: 0.60 rad
- FNUM: 2.2
- DIAG: 7.0 mm
- Elements: 6



- HFOV: 0.55 rad
- FNUM: 2.4
- DIAG: 6.5 mm
- Elements: 6





- HFOV: 0.45 rad
- FNUM: 2.8
- DIAG: 6.0 mm
- Elements: 6





**AutoLens! [?] results across five 6-element mobile lens design targets.** From top to bottom, the design difficulty is progressively reduced by jointly relaxing the half field of view, aperture, and sensor size: (0.75 rad,  $F/1.8$ , 8.0 mm), (0.70 rad,  $F/2.0$ , 7.66 mm), (0.60 rad,  $F/2.2$ , 7.0 mm), (0.55 rad,  $F/2.4$ , 6.5 mm), and (0.45 rad,  $F/2.8$ , 6.0 mm). Each row shows the optimized lens layout, MTF curves, and spot diagrams produced by AutoLens.

Lens Design



- HFOV: 0.75 rad
- FNUM: 1.8
- DIAG: 8.0 mm
- Elements: 6





- HFOV: 0.70 rad
- FNUM: 2.0
- DIAG: 7.66 mm
- Elements: 6





- HFOV: 0.60 rad
- FNUM: 2.2
- DIAG: 7.0 mm
- Elements: 6



- HFOV: 0.55 rad
- FNUM: 2.4
- DIAG: 6.5 mm
- Elements: 6





- HFOV: 0.45 rad
- FNUM: 2.8
- DIAG: 6.0 mm
- Elements: 6



**GPT-5.4 results across five 6-element mobile lens design targets.** From top to bottom, the design difficulty is progressively reduced by jointly relaxing the half field of view, aperture, and sensor size: (0.75 rad,  $F/1.8$ , 8.0 mm), (0.70 rad,  $F/2.0$ , 7.66 mm), (0.60 rad,  $F/2.2$ , 7.0 mm), (0.55 rad,  $F/2.4$ , 6.5 mm), and (0.45 rad,  $F/2.8$ , 6.0 mm). Each row shows the optimized lens layout, MTF curves, and spot diagrams produced by GPT-5.4.

Lens Design



- HFOV: 0.75 rad
- FNUM: 1.8
- DIAG: 8.0 mm
- Elements: 6



Cannot compute when chief ray cannot be traced

EP F2.0 Mobile Lens 4/14/2026	Zemax	EP F2.0 Mobile Lens: 4/14/2026 Legend items refer to wavelengths	Zemax
Legend items refer to Field positions	5.2mm Configuration 1 of 1	Cannot compute when chief ray cannot be traced.	5.2mm Configuration 1 of 1



- HFOV: 0.70 rad
- FNUM: 2.0
- DIAG: 7.66 mm
- Elements: 6



Cannot compute when chief ray cannot be traced

EP F2.0 Mobile Lens 4/14/2026	Zemax	EP F2.0 Mobile Lens: 4/14/2026 Legend items refer to wavelengths	Zemax
Legend items refer to Field positions	5.2mm Configuration 1 of 1	Cannot compute when chief ray cannot be traced.	5.2mm Configuration 1 of 1




- HFOV: 0.60 rad
- FNUM: 2.2
- DIAG: 7.0 mm
- Elements: 6



Cannot compute when chief ray cannot be traced




EP F2.0 Mobile Lens 4/14/2026	Zemax	EP F2.0 Mobile Lens: 4/14/2026 Legend items refer to wavelengths	Zemax
Legend items refer to Field positions	4.3mm Configuration 1 of 1	Cannot compute when chief ray cannot be traced.	4.3mm Configuration 1 of 1

- HFOV: 0.55 rad
- FNUM: 2.4
- DIAG: 6.5 mm
- Elements: 6



EP F2.0 Mobile Lens 4/14/2026	Zemax	EP F2.0 Mobile Lens: 4/14/2026 Units are μm. Legend items refer to wavelengths	Zemax
Data for 0.4881 to 0.6169 μm	1.0mm Configuration 1 of 1	Field: 1 2 3 RMS radius: 180.100 157.111 488.100 GDQ radius: 281.194 883.860 920.100 Scale bar: 2000.00 Reference: Chief Ray	5.2mm Configuration 1 of 1

- HFOV: 0.45 rad
- FNUM: 2.8
- DIAG: 6.0 mm
- Elements: 6




EP F2.0 Mobile Lens 4/14/2026	Zemax	EP F2.0 Mobile Lens: 4/14/2026 Units are μm. Legend items refer to wavelengths	Zemax
Data for 0.4881 to 0.6169 μm	1.0mm Configuration 1 of 1	Field: 1 2 3 RMS radius: 180.100 157.111 488.100 GDQ radius: 281.194 883.860 920.100 Scale bar: 2000.00 Reference: Chief Ray	5.2mm Configuration 1 of 1



**Gemini results across five 6-element mobile lens design targets.** From top to bottom, the design difficulty is progressively reduced by jointly relaxing the half field of view, aperture, and sensor size: (0.75 rad,  $F/1.8$ , 8.0 mm), (0.70 rad,  $F/2.0$ , 7.66 mm), (0.60 rad,  $F/2.2$ , 7.0 mm), (0.55 rad,  $F/2.4$ , 6.5 mm), and (0.45 rad,  $F/2.8$ , 6.0 mm). Each row shows the optimized lens layout, MTF curves, and spot diagrams produced by Gemini.

Lens Design

- HFOV: 0.75 rad
- FNUM: 1.8
- DIAG: 8.0 mm
- Elements: 6



- HFOV: 0.45 rad
- FNUM: 2.8
- DIAG: 6.0 mm
- Elements: 6



**Qwen results across five 6-element mobile lens design targets.** From top to bottom, the design difficulty is progressively reduced by jointly relaxing the half field of view, aperture, and sensor size, ranging from (0.75 rad,  $F/1.8$ , 8.0 mm) to (0.45 rad,  $F/2.8$ , 6.0 mm). For the other targets, Qwen fails to generate meaningful lens prescriptions, and the resulting files cannot be reliably analyzed in Zemax. Each valid row shows the corresponding lens layout, MTF curves, and spot diagrams.

## ACKNOWLEDGMENTS

This work used Delta at National Center for Supercomputing Applications [award OAC 2005572], and Google Cloud Platform & Microsoft Azure at CloudBank through allocation CIS260120 from the Advanced Cyberinfrastructure Coordination Ecosystem: Services & Support (ACCESS) program, which is supported by U.S. National Science Foundation grants #2138259, #2138286, #2138307, #2137603, and #2138296.

This research used the Delta advanced computing and data resource which is supported by the National Science Foundation (award OAC 2005572) and the State of Illinois. Delta is a joint effort of the University of Illinois Urbana-Champaign and its National Center for Supercomputing Applications.

This work used Google Cloud Platform and Microsoft Azure through the CloudBank project, which is supported by National Science Foundation grant #1925001.



**Michael Shell** Biography text here.

**John Doe** Biography text here.